

56SMKIT

5.6" LCD MONITOR KIT



PRODUCT FEATURES

- 5.6" ACTIVE MATRIX TFT DISPLAY
- DUAL VIDEO AND AUDIO COMPOSITE INPUTS
- INCLUDES RECHARGEABLE BATTERY & CHARGER

SPECIFICATIONS

RESOLUTION	960 X 234
BRIGHTNESS	200 CD/M2
CONTRAST RATIO	150:1
VIEW ANGLE	R/L: +/-45 U: +10 D: -30
SYSTEM	NTSC/PAL SWITCHABLE
VIDEO INPUT	RCA X 2 , 1 VP-P, 75 OHMS
AUDIO INPUT	RCA X 2, 30M VP-P
AUDIO OUTPUT	0.5 WATT MAX (8 OHMS)
VIDEO/AUDIO CONNECTOR	MINI PHONE JACK W/MINI PHONE PLUG TO RCA PLUG ADAPTER
USER CONTROL	MODE, LEFT/RIGHT, POWER, OSD
BATTERY	12VDC, 1.8AH CHARGEABLE
CHARGER	YES
POWER	12VDC @ 400MA
OPERATION TEMPERATURE	14F-122F
DIMENSION (W X H X D)	6.3" X 5.2" X 1.4"