

Product Specifications

CVIOD-EL1MPIR50

Features:

- 1/3" 1.3Megapixel CMOS
- 25/30/50/60fps@720P
- High speed, long distance real-time transmission
- HD and standard definition switch.
- OSD Menu, control over coaxial cable
- Day/Night(ICR), AWB, AGC, BLC, 3D-DNR,
- 3.6mm fixed lens
- Max. IR LEDs length 20m, Smart IR
- IP66, DC12V



Image Sensor	1/3" 1.3Mega CMOS
Effective Pixels	1280(H)×960(V)
Video Frame Rate	1280×720@25 fps, 1280×720@30 fps, 1280×720@50 fps, 1280×720@60 fps
Synchronization	Internal
Min. Illumination	0.01Lux@F1.2(0Lux IR LED on)
Video Output	1-channel BNC HDCVI high definition video output/ CVBS standard definition video output (Can switch)
Max. IR LEDs Length	20m, Smart IR
Day/Night	Auto(ICR)/B&W/Color
Noise Reduction	3D/2D
OSD Menu	Support
Focal Length	3.6mm
Mount Type	M12
Power Supply	DC12V±10%
Power Consumption	Max 3.5W
Working Environment	-30°C~+60°C/ Less than 95%RH (no condensation)
Transmission Distance	Over 500m via 75-3 coaxial cable
Ingress Protection	IP66
Dimensions	Φ113.6mm x 85.4mm