

# CVIPTZ-EL4IRL30X-D2

4MP 30x IR PTZ HDCVI Camera



- 1/3" 4Megapixel CMOS
- Powerful 30x optical zoom
- 120dB true WDR, 3D DNR
- Max. 25/30fps@4M/1080P, 25/30/50/60fps@720P
- IR distance up to 100m
- IP66



## System Overview

Featuring with powerful optical zoom and accurate pan/tilt/zoom performance, the CVIPTZ-EL4IRL30X-D2 series PTZ camera can provide a large monitoring range and great detail. The camera delivers 4MP resolution at 25/30 fps, with 30x optical zoom. This PTZ is equipped with quick and smooth control, high quality image and good protection, which means it can meet most of the requirements of video surveillance applications.

## Functions

### Simplicity

HDCVI technology inherits the feature of simplicity from traditional analog surveillance system, making it a best choice for your protection. The HDCVI system can seamlessly upgrade the traditional analog system without replacing existing coaxial cabling. The plug and play approach enables full HD video surveillance without the hassle of configuring a network.

### Wide Dynamic Range

Embedded with industry leading Wide Dynamic Range (WDR) technology, vivid pictures are achieved even in the most intense contrast lighting conditions. For applications with both bright and low lighting conditions that change quickly, true WDR (120dB) optimizes both the bright and dark areas of a scene at the same time to provide usable video.

### Environmental

With a temperature range of -40 °C to +70 °C (-40 °F to +158 °F), the camera is designed for extreme temperature environments. Subjected and certified to rigorous dust and water immersion tests, the IP66 rating makes it suitable for demanding outdoor applications.

### Protection

This camera suits even the harsh conditions for outdoor applications. Its 6KV lightning rating provides protection against the camera and its structure from the effects of lightning.

# CVIPTZ-EL4IRL30X-D2

## Technical Specification

### Camera

|                          |                                             |
|--------------------------|---------------------------------------------|
| Image Sensor             | 1/3" CMOS                                   |
| Effective Pixels         | 2592(H) x 1520(V), 4 Megapixels             |
| Scanning System          | Progressive                                 |
| Electronic Shutter Speed | PAL: 1/3s~1/30,000s<br>NTSC: 1/4s~1/30,000s |
| Minimum Illumination     | Color: 0.05Lux@F1.6; 0Lux@F1.6 (IR on)      |
| S/N Ratio                | More than 55dB                              |
| IR Distance              | Distance up to 100m (328ft)                 |
| IR On/Off Control        | Auto/Manual                                 |
| IR LEDs                  | 4                                           |

### Lens

|                      |               |
|----------------------|---------------|
| Focal Length         | 4.5mm~135mm   |
| Max. Aperture        | F1.6 ~ F4.4   |
| Angle of View        | H: 60° ~ 2.2° |
| Optical Zoom         | 30x           |
| Focus Control        | Auto/Manual   |
| Close Focus Distance | 100mm~ 1000mm |

### DORI Distance

\*Note: The DORI distance is a "general proximity" of distance which makes it easy to pinpoint the right camera for your needs. The DORI distance is calculated based on sensor specification and lab test result according to EN 62676-4 which defines the criteria for Detect, Observe, Recognize and Identify respectively.

|               |               |              |             |
|---------------|---------------|--------------|-------------|
| Detect        | Observe       | Recognize    | Identify    |
| 2700m(8858ft) | 1080m(3543ft) | 540m(1772ft) | 270m(886ft) |

### PTZ

|                      |                                                                                     |
|----------------------|-------------------------------------------------------------------------------------|
| Pan/Tilt Range       | Pan: 0° ~ 360° endless; Tilt: -15° ~ 90°,auto flip 180°                             |
| Manual Control Speed | Pan: 0.1° ~300° /s; Tilt: 0.1° ~200° /s                                             |
| Preset Speed         | Pan: 400° /s; Tilt: 300° /s                                                         |
| Presets              | 300                                                                                 |
| PTZ Mode             | 5 Pattern, 8 Tour, Auto Pan ,Auto Scan                                              |
| Speed Setup          | Human-oriented focal Length/ speed adaptation                                       |
| Power up Action      | Auto restore to previous PTZ and lens status after power failure                    |
| Idle Motion          | Activate Preset/ Scan/ Tour/ Pattern if there is no command in the specified period |
| Protocol             | DH-SD, Pelco-P/D (Auto recognition)                                                 |

### Video

|              |                                                                                                |
|--------------|------------------------------------------------------------------------------------------------|
| Resolution   | 4M(2592x1520) / 1080P(1920x1080) / 720P(1280x720)                                              |
| Frame Rate   | 25/30fps@4M/1080P, 25/30/50/60fps@720P                                                         |
| Video Output | 1-channel BNC high definition video output/ CVBS standard definition video output (switchable) |

|                        |                                |
|------------------------|--------------------------------|
| Day/Night              | Auto(ICR) / Color / B/W        |
| OSD Menu               | Support                        |
| Backlight Compensation | BLC / HLC / WDR (120dB)        |
| White Balance          | Auto,ATW,Indoor,Outdoor,Manual |
| Gain Control           | Auto / Manual                  |
| Noise Reduction        | Ultra DNR (2D/3D)              |
| Digital Zoom           | 16x                            |
| Flip                   | 180°                           |
| Privacy Masking        | Up to 24 areas                 |

### Certifications

|                |                                                                                                                  |
|----------------|------------------------------------------------------------------------------------------------------------------|
| Certifications | CE: EN55032/EN55024/EN50130-4<br>FCC: Part15 subpartB,ANSI C63.4- 2014<br>UL: UL60950-1+CAN/CSA C22.2,No.60950-1 |
|----------------|------------------------------------------------------------------------------------------------------------------|

### Interface

|                 |              |
|-----------------|--------------|
| Video Interface | 1            |
| Audio Interface | 1 channel in |
| RS485           | 1            |
| Alarm I/O       | 2/1          |

### Electrical

|                   |                 |
|-------------------|-----------------|
| Power Supply      | AC24V/3A(±10%)  |
| Power Consumption | 13W,23W (IR on) |

### Environmental

|                      |                                                  |
|----------------------|--------------------------------------------------|
| Operating Conditions | -40°C ~ 70°C (-40°F ~ +158°F) / Less than 95% RH |
| Ingress Protection   | IP66                                             |
| Vandal Resistance    | N/A                                              |

### Construction

|              |                    |
|--------------|--------------------|
| Casing       | Metal              |
| Dimensions   | Φ186(mm) x 309(mm) |
| Net Weight   | 3.5kg(7.72lb)      |
| Gross Weight | 6.8kg(14.99lb)     |

# CVIPTZ-EL4IRL30X-D2

## Accessories

Included:



WM-EL300S  
Wall Mount



PFA110  
Mount Adapter



AC24V/3A  
Power Supply


Optional:



PM-EL150  
Pole Mount






CM-EL300C  
Ceiling Mount



CM-EL151  
Corner Mount



PB-EL303S  
Parapet Mount

| Ceiling Mount                                                                       | Pole Mount                                                                          |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| MA-EL110 + CM-EL300C                                                                | MA-EL110 + WM-EL300S + PM-EL150                                                     |
|   |   |
| Corner Mount                                                                        | Parapet Mount                                                                       |
| MA-EL110 + WM-EL300S + CM-EL151                                                     | MA-EL110 + PB-EL303S                                                                |
|  |  |

## Dimensions (mm)

