

2.4MP HDCVI Indoor/ Outdoor Vandal Dome Camera Vari-focal Motorized

HDCVI
High Definition Composite Video Interface

Model Number
ELI-ACVI-VD24-312HMA



Key Features:

- 1/2.8" 2.4Megapixel CMOS
- High rate, long-distance, real-time transmission
- HD and standard definition switchable
- Day/Night(ICR), AWB, AGC, BLC, 3D-DNR
- Audio, Alarm, Heater
- Night vision up to 98 feet
- 2.7~12mm motorized lens, Auto Iris
- Power supply Dual: AC24V/ DC12V

Specifications are subject to change without prior notice.

Model Number	ELI-ACVI-VD24-312HMA
Camera	
Image Sensor	1/2.8" 2.4Megapixel CMOS
Effective Pixels	1984(H)×1225(V)
Electronic Shutter	1/3s~1/100,000s
Video Frame Rate	25/30/50/60fps@720P; 25/30fps@1080P
Synchronization	Internal
Mini. Illumination	0.05Lux@F1.2(AGC ON), 0Lux IR on
Video Output	1-channel BNC HDCVI high definition video output / CVBS standard definition video output (Can switch) Tester out (1-channel BNC HDCVI high definition video output / CVBS standard definition video output)
Camera Features	
Max. IR LEDs Length	30m, (98 feet) Smart IR
Day/Night	Auto(ICR) / Color / B/W
Noise Reduction	2D/3D
OSD Menu	Support
Lens	
Focal Length	2.7~12mm
Angle of View	H: 105.5°~32.9°
Lens Type	Motorized / Auto Iris
Mount Type	Φ 14
Auxiliary Functions	
Alarm	1 channel in/out
Audio	1 channel in
Heater	yes
General	
Power Supply	AC24V±10% / DC12V±10%
Power Consumption	9.6W
Working Environment	-40°C~+60°C / Less than 95%RH (no condensation)
Transmission Distance	Over 300m via 75-3 coaxial cable
Ingress Protection	IP66 & IK10
Dimensions(W×D×H)	Φ150mm×119.1mm
Weight	1.8lbs (0.8kg)

