

1080p Economy Bullet IP with IR

Mini Economy Bullet with IR
MODEL NUMBER ELI-SIP-EB21-4R



Key Features:

- 1080p Resolution
- Day/Night Mini Bullet with IR LEDs
- Weather-Proof IP66
- Fixed 3.6mm Fixed Lens
- D-WDR
- Remote Monitoring for mobile device and Web Browsers



TechProSecurity.com | 866-573-8878

ELI-SIP-EB21-4R	
Sensor	Aptina AR0330 1/3" CMOS
Max Resolution/ FPS	1920x1080 @ 30fps
Min. illumination	Color: 0.2Lux@f.12, B/W: 0Lux@ f1.2
Day / Night	True Day / Night with ICR Filter.
D-WDR	78.4dB
IR LEDs	2pcs High Powered Super Flux LED 850nm 6-10 meters (19 - 32 feet)
Lens	3.6mm
Electronic Shutter	Auto / User 1/5 - 1/20,0000 ; 50/60Hz software selectable
VIDEO	
Compression	H.264 High Profile (Support Baseline Profile)/MJPEG.
Bit Rate (CBR/VBR)	Stream1 500Kbps-12Mbps; Stream2 100Kbps-6MMbps
Quality Setting (VBR)	1 - 9 (9 Highest)
Multi- Streaming	User setting of stream 1/2 at supported resolutions
Brightness /Sharpness	Variable 0~100 / 0~100
Gain Control	Auto / Fixed 8~102dB
Orientation	Horizontal Mirror / Vertical Flip
Text Overlay	Time / Date / Camera / Custom OSD
Masking	4 User defined masking areas < 8% of total picture
NETWORK	
Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
Compliance	Onvif v2.2 Profile-S
Web language	English, Chinese
Network Protocol	IPV4, HTTPS, TCP/UDP, RTSP, FTP, DHCP, PPOE, DDNS, SMTP
Memory Card	N/A
Max user Access	6 (max 2 Users for 1080p)
GENERAL	
Power	DC 12v/ POE 802.3af (POE Optional)
Power Consumption	2.5W max (IR LED OFF) 5W max (IR LED On) 7W Max (Heater On)
Temperature	-20 degrees C ~ +55 degrees C (about -10 degrees C heater will turn on)
Operating Humidity	0% - 95% RH
Approvals	CE/ FCC/ RoHS Compliant/ IP66
Product Dimensions	6.6 x 2.4 in
Product weight	1.3 lbs

*Design and specifications are subject to change without notice.