

2MP Economy Mini- Dome Camera with IR


"The Hockey Puck"

Model: ELI-SIP-EMVD-21-4R

Key Features:

- 2MP resolution (1920 x 1080)
- Vandal Resistant IK10
- Weatherproof IP66
- Real-time frame rate up to 30fps
- Day/Night with ICR
- Audio Input & Output on Cable
- 12VDC/PoE

*Specifications are subject to change without Notice.



High Resolution

Clear, sharp 2MP resolution. | 1920x1080 @ 30fps
3.6mm Fixed Lens






Long Range Night Vision

Equipped with 1pc Super Flux IR LED for a range up to 20 feet (6 Meters).



Built-in Video Storage

Add Edge recording by installing an SD Card up to 64GB. Free VMS software for accessing in-camera video storage is included.



*Design and specifications are subject to change without notice.



TechProSecurity.com | 866-573-8878

2MP Economy Mini- Dome Camera with IR

"The Hockey Puck"

Model Number	ELI-SIP-EMVD-21-4R
Sensor	CMOS 1/3" with 100db WDR
Max Res./ Max Frame Rate	1920x1080 @ 30fps
Min. Illumination	Color: 0.2Lux@f.12, B/W: 0Lux@ f1.2
Camera	
Day / Night	True Day / Night with ICR Filter.
Lens	3.6mm Fixed Mega Pixel
IR LED	1pc High Powered Super Flux LED 850nm
IR Distance	6 Meters (20 feet)
Video Output	Setup / Service BNC Video supported internal connector with dangle cable supplied
Electronic Shutter	Auto / User 1/5 - 1/20,000 ; 50/60Hz software selectable
Video	
Compression	H.264 High Profile (Support Baseline Profile)/MJPEG.
Streaming	Stream1 Full Resolution, Stream2 VGA / D1 / CIF or QCIF
Quality Setting (VBR)	1 - 9 (9 Highest)
Multi- Streaming	User setting of stream 1/2 at supported resolutions
Brightness / Sharpness	Variable 0~100 / 0~100
Gain Control	Auto / Fixed 8~102dB
Orientation	Horizontal Mirror / Vertical Flip
Text Overlay	Time / Date / Camera / Custom OSD
Masking	5 User defined masking areas < 8% of total picture
Network	
Ethernet	1 Ethernet (10/100 Base-T) RJ45 Connector
Compliance	Onvif v2.2 (Profile S)
Network Protocol	IPV4, HTTPS, TCP/UBP, RTSP, FTP, DHCP, PPoE, DDNS, SMTP
Web Language	English, Chinese, Russian, Polish
Recording	Local Micro SD Memory, Remote FTP server, TCP/UDP CMS, RTSP connection .



General	
Power	12V DC Terminal Input / PoE 802.3af Class 3 5.1W / Max 8.1W (LED On)
Temperature	Operating: 14°F to 131°F (-10°C to 55°C) Storage: -4°F to 140°F (-20°C to 60°C)
Operating Humidity	10% - 85% RH
Approvals	CE / FCC / RoHS Compliant / IP65 / IK10
Dimensions	100 x 53 mm (4" x 2")
Product Weight	0.3kg / 0.66lb

