

3MP Mini- Dome Camera with IR

"The Hockey Puck"

Model: ELI-SIP-MVD3-2R

Key Features:

- 3MP resolution (2048x1536)
- Vandal Resistant IK10
- Weatherproof IP66
- Real-time frame rate up to 30fps
- Day/Night with ICR
- Alarm and Audio Input & Output on Cable
- 12VDC/PoE

*Specifications are subject to change without Notice.



High Resolution

Clear, sharp 3MP resolution. | 2048x1536 @ 20fps
2.8mm Fixed Lens






Long Range Night Vision

Equipped with 1pc Super Flux IR LED for a range up to 20 feet (6 Meters).



Built-in Video Storage

Add Edge recording by installing an SD Card up to 64GB. Free VMS software for accessing in-camera video storage is included.



3MP Mini- Dome Camera with IR “The Hockey Puck”

Model Number	ELI-SIP-MVD3-2R
Sensor	Aptina 1/3" WDR CMOS
Max Res./ Max Frame Rate	2048x1536 / 20fps
Min. Illumination	0.5 Lux (Color) (0.02 Lux B/W) (0 Lux IR LED On)
Camera	
Day / Night	True Day / Night with ICR Filter.
Lens	2.8mm Fixed Mega Pixel IR Coated
Field of View (H / V / D)	77° / 54° / 100.2°
IR LED	1pc High Powered Super Flux LED 850nm
IR Distance	6 Meters (20 feet)
Video Output	Setup / Service BNC Video supported internal connector with dangle cable supplied
Electronic Shutter	Auto / User 1/5 - 1/50,000 ; 50/60Hz software selectable
Video	
Compression	H-264 High/Main/Base Profile. Stream1 H-264, or MJPEG.
Streaming	Stream1 Full Resolution, Stream2 VGA / D1 / CIF or QCIF selectable
Quality Setting (VBR)	1 - 9 (9 Highest)
I Frame	User selection value
Brightness / Sharpness	Variable 0~100 / 0~100
Gain Control	Auto / Fixed 8~102dB
Orientation	Horizontal Mirror / Vertical Flip
Text Overlay	Time / Date / Camera / Custom OSD
Masking	5 User defined masking areas < 8% of total picture

Network	
Ethernet	1 Ethernet (10/100 Base-T) RJ45 Connector
TCP/IP	IPv4 / IPv6 (DHCP / Fixed)
Compliance	Onvif v2.2 (Profile S)
RTSP Video	Standard RFC2326, Support Quicktime / VLC Player. User security authentication (Enabled / Disabled)
Web Language	English, Chinese, Russian, Polish
Recording	Local Micro SD Memory, Remote FTP server, TCP/UDP CMS, RTSP connection .
Network Protocols:	HTTP, TCP/IP, UDP/IP, RTSP, FTP, DHCP, NTP, PPPoE, NTP. Unicast and Multicast supported. Video streaming from SDK & NVMS / NVR software or 3rd party applications.
Audio	
Input / Output	Optional Microphone: 1 x RCA Input / 1 x RCA Output @ 1V Line Level
Audio Compression	G711 A-law, G711 u-law , RAW_PCM
General	
Power	12V DC Terminal Input / PoE 802.3af Class 3 5.1W / Max 8.1W (LED On)
Temperature	Operating: 14°F to 131°F (-10°C to 55°C) Storage: -4°F to 140°F (-20°C to 60°C)
Operating Humidity	10% - 85% RH
Approvals	CE / FCC / RoHS Compliant / IP65 / IK10
Dimensions	100 x 53 mm (4" x 2")
Product Weight	0.3kg / 0.66lb

