

IP Mini Vandal Dome Camera with IR "The Hockey Puck"

Model Number	Resolution & Options
ELI-SIP-MVD3-4R	3mp (2048x1536)



Long Range Night Vision

Equipped with 1pc Super Flux IR LED for a range of up to 6 meters.



Built-in Video Storage

Add Edge recording by installing an SD Card up to 64GB. Free VMS software for accessing in-camera video storage is included.




High Resolution

Clear, sharp 3MP resolution. 2.8mm Fixed Lens



eLine's S Series of IP Cameras use the Onvif standard to give end users the greatest flexibility and compatibility in surveillance system components and software.

Read more at www.onvif.org



Free NVMS Software is included






TechProSecurity.com | 866-573-8878

IP Mini Vandal Dome Camera with IR “The Hockey Puck”

Model No.	ELI-SIP-MVD-3-4R
Camera	
Sensor	Aptina 1/3" WDR CMOS
Max Resolution / FPS	2048x1536/ 30fps
Min Illumination	0.5LUX @ f1.2 (Color) (0 Lux IR LED On)
Day / Night	True Day / Night with ICR Filter
Lens	2.8mm Fixed MegaPixel IR Coated. Angle 89°+4°(D)x70°(H) x51.9°(V)
Field of View	77 ° / 54 ° / 100.2 °
IR LEDs	1 pc Super Flux IR LED 850nm for 6 Meters (20 feet)
Video Output	Service BNC Video with IP OSD using supplied dangle cable
Electronic Shutter	Auto / User 1/5-1/50 0000; 50/60Hz software selectable
Parameters	
Compression	H.264 High Profile (Support Baseline Profile) / MJPEG
Bit Rate (CBR/VBR)	Stream1 50Kbps - 12Mbps; Stream2 10Kbps - 6Mbps; Stream3 (MJPEG Fixed)
Quality Setting	1-9 (9 Highest)
Multi-Streaming	Three simultaneous streams, two with H.264, one with MJPEG Stream
Brightness / Sharpness	Variable 0~100 / 0~100
Gain Control	Auto / Fixed 8~102db
Orientation	Horizontal Mirror / Vertical Flip
Text Overlay	Time / Date / Camera / Custom OSD
Masking	3 User Defined masking areas < 8% of total picture
Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
TCP/IP	IPv4 / IPv6
Compliance	Onvif v2.2 Profile-S
RTSP Video	Standard RFC2326, Support Quick Time / VLC Player. User security authentication (Enabled / Disabled)
Web Language	English, Chinese, Russian, Polish

Recording Simultaneous	Local Micro SD Memory, Remote FTP server, TCP/UDP CMS, RTSP connection (Stream 1, 2 or 3)
Network Protocols	HTTP, TCP/IP, UDP/IP, RTSP, FTP, DHCP, NTP, PoE, NTP. Unicast and Multicast supported.
Memory Card Slot	Internal memory card supports Max 64GB. Supports Edge Recording.
Audio	
Input/Output	Optional Microphone: 1 x RCA Input / 1 x RCA Output @ 1v Line Level
Audio Compression	G711 A-Law, G711 U-Law, RAW_PCM
General	
Power	12VDC @ 335mA (IR LED On) / PoE Class 3 on ethernet
Temperature	Operating -10°C to 55°C (down to -40°F with heater) Storage -20°C to 60°C
Humidity	10% - 85% RH
Approvals	CE / FCC / RoHS Compliant / IP66 / IK10
Product Dimensions	100 x 53 mm
Product Weight	0.3kg/0.66lb



TechProSecurity.com | 866-573-8878