


SIP Series NVR - 4 Ch PoE, High Resolution 1080p

Model Options: ELI-SIP-NVR4-POE | Model: ELI-SIP-NVR4-POE-D



Recording

- High Profile H.264 Compression
- High Definition output HDMI or VGA up to 1080p/720p
- 4-channels 1080p 30fps
- 4-channel PoE = Direct connect to camera



Intuitive Software

- Embedded InView GUI with full mouse control
- Easy to use GUI, low learning curve for users
- Multi-NVR system setup - manage up to 256 NVRs
- Smart Search
- Easy Export and Remote Saving
- ONVIF Standard Compliant



Display

- Multiple Monitor Support
- Remote View and Playback from Web Browser
- Remote Apps for iPhone and Android

1 Hard Drive up to 4TB Max
ELI-SIP-NVR4-POE-D



2 Hard Drives up to 4TB each
ELI-SIP-NVR4-POE



*Ask about our rack mount option



TechProSecurity.com | 866-573-8878

SIP Series NVR - 4 Ch PoE, High Resolution 1080p

VIDEO		ELI-SIP-NVR4-POE-D	ELI-SIP-NVR4-POE
Recording	4ch 1080p/720p real time video input		
Output Display	Single screen: 1x1080p /720p with Tour Quad display of 1080p/720p resolutions Split screen: 1/4 layout for 1080p/720p Live video		
Output Resolutions	VGA resolution: 1024x768, 1280x1024, 1600x1200 HDMI resolution: 1280x720p, 1920x1080p		
Video Decoding	Up to H.264 (ISO/IEC 14496-10) high profile to level 4.2		
Decoding	NTSC: 30 fps PAL: 25 fps CBR (Constant Bit Rate), VBR (Variable Bit Rate) as defined by IP Device 720p: Standard 3Mbps 720p @ 30fps VGA quality (substream) 1080p: Standard 4.5Mbps 1080p @ 30fps VGA quality (substream)		
Rate Control			
Stream Input			
Playback	4ch 1080P/720P		
STORAGE			
HDD	1 x HDD Max 4TB	2 x HDD Max 8TB with 2pcs 4TB	
Recording Real-Time	1080p: average bitrate 4.5Mbps. Up to 4 Channel		
Recording Method	Constant Recording / Motion Detection		
CONNECTIONS			
Power Switch	Power on from connected power source / power off software control with authentication.		
Network	1 x RJ45 100Meg. 4x 100Meg PoE ports		
Video Outputs	VGA DB15 and HDMI 19pin Connectors		
Audio Output	3.5mm linear audio output, support G711 A / G711 U		
USB	2 USB 2.0, 1 USB Mouse, 1 USB for Keyboard (Keyboard optionally used for ease of name entry or setup)		

NETWORK		ELI-SIP-NVR4-POE-D	ELI-SIP-NVR4-POE
Web Server	Embedded serer supporting (Multi Browser Support) 4ch Live cameras. 1ch real-time search and playback		
Network Protocols	RTP/RTCP, TCP/UDP, HTTP, DHCP, DNS,NTP, RTMP, Sunell SDK, ONVIF		
Ports	4 PoE ports		
AUDIO			
Output	Support for the rear panel LINE OUT via 3.5mm Connector		
Recording	G711 A-Law, G711 U-Law		
PHYSICAL			
Power	External PSU 48V/1.45A		External 12V/5A PSU for NVR, External PSU 48V/1.04A for PoE interface
Cooling	Main chip cooling using heat sinks, plus thermal controlled intelligent cooling fan.		
Operating Humidity	20%-80% RH		
Operating Temperature	32F~113F		
Approvals	CE / FCC / RoHS Compliant		
Product Dimensions LWH	270mmx175mmx50mm		220mm x 150mm x 100mm
Product Weight	665g/1.4lb		2.38kg / 5.251lb
Software Client	PC Client Application for remote monitor/ playback of NVR device iOS/ Android app. Full device settings live monitoring & recording playback from NVR		

*Design and specifications are subject to change without notice.

Model No. ELI-SIP-NVR4-POE Ask about Rack Mount Options*
Model No. ELI-SIP-NVR4-POE-D

TechProSecurity.com | 866-573-8878



SIP Series NVR - 4 Ch PoE, High Resolution 1080p

ELI-SIP-NVR Screen Diagram

