


SIP Series NVR - 8 Ch PoE, High Resolution 1080p

ELI-SIP-NVR8-POE



Recording

- High Profile H.264 Compression
- High Definition output HDMI or VGA up to 1080p/720p
- 2 Avail HDDs (8TB max)
- 8-channels 1080p 30fps
- 8-channel PoE = direct camera connect



Intuitive Software

- Embedded InView GUI with full mouse control
- Easy to use GUI, low learning curve for users
- Multi-NVR system setup - manage up to 256 NVRs
- Smart Search
- Easy Export and Remote Saving
- ONVIF Standard Compliant



Display

- Multiple Monitor Support
- Remote View and Playback from Web Browser
- Remote Apps for iPhone and Android



*Ask about our rack mount option



TechProSecurity.com | 866-573-8878

SIP Series NVR - 8 Ch PoE, High Resolution 1080p

VIDEO	
Recording	8ch 1080p/720p real time video input
Output Display	Single screen: 1x1080p /720p with Tour Quad display of 1080p/720p resolutions Split screen: 1/4 layout for 1080p/720p Live video
Output Resolutions	VGA resolution: 1024x768, 1280x1024, 1600x1200 HDMI resolution: 1280x720p, 1920x1080p
Video Decoding	Up to H.264 (ISO/IEC 14496-10) high profile to level 4.2
Decoding	NTSC: 30 fps PAL: 25 fps
Rate Control	CBR (Constant Bit Rate), VBR (Variable Bit Rate) as defined by IP Device
Stream Input	720p: Standard 3Mbps 720p @ 30fps VGA quality (substream) 1080p: Standard 4.5Mbps 1080p @ 30fps VGA quality (substream)
Playback	4ch 1080P/720P
STORAGE	
HDD	2 x HDD Max 8TB with each HDD 4TB
Recording Time	720p: average bit-rate 3Mbps with 4Channel Up to 30Days 1080p: average bitrate 4.5Mbps with 4Channel Up to 21Days
Recording Method	Constant Recording / Motion Detection
CONNECTIONS	
Power Switch	Power on from connected power source / power off software control with authentication.
Video Outputs	One DVI Output converter to VGA/HDMI
Audio Output	3.5mm linear audio output, support G711 A-Law / G711 U-Law
USB	2 USB 2.0, 1 USB Mouse, 1 USB for Keyboard (Keyboard optionally used for ease of name entry or setup)

NETWORK	
Network Control	Thermal controlled fan, silent bearing type
Web Server	Embedded server supporting Flash Video RTMP server (Multi Browser Support) 4ch Live cameras real-time.
Network Protocols	RTP/RTCP, TCP/UDP, HTTP, DHCP, DNS, NTP, RTMP, Sunell SDK, ONVIF
Network Interface	1 RJ45 10M/100M network port, 8 RJ45 10M/100M POE network port
Ports	8 PoE ports
AUDIO	
Output	Support for the rear panel LINE OUT
Recording	G711 A-Law, G711 U-Law
PHYSICAL	
Power	100-240V/47-63Hz 3A
Cooling	Main chip cooling using heat sinks, plus thermal controlled intelligent cooling fan.
Operating Humidity/Temp	0% to 90% / 32F~113F
Approvals	CE / FCC / RoHS Compliant
Product Dimensions LWH	14.64" x 12" x 1.75"
Product Weight	7.36lb
Software Client	Supplied CD with PC NVMS software for remote view / setup of NVR (Not required to use product)

*Design and specifications are subject to change without notice.

ELI-SIP-NVR8-POE

Rack Mount Option Also Available



SIP Series NVR - 8 Ch PoE, High Resolution 1080p

ELI-SIP-NVR Screen Diagram

