

4K Ultra HD SIP2 series NVRs

ELI-SIP2-NVR16

UP TO
12MP
PREVIEW &
PLAYBACK

4K
Real Time

Key Features:

- 16 Channel IP camera input
- Up to 12Mp resolution preview&playback
- H.265/H.264/MJPEG dual codec decoding
- Max 256Mbps incoming bandwidth
- HDMI/VGA simultaneous video output
- 16 channel synchronous realtime playback, GRID interface
- Support Multi-brand network cameras
- ONVIF Version 2.4 conformance
- 3D intelligent positioning with compatible PTZ
- Support 4 SATA HDDs up to 24TB, 3 USB, 1 eSATA port
- Support IPC UPnP
- Support P2P, QR code scan setup
- Remote monitoring with web viewer and Mobile devices

Specifications are subject to change without prior notice.



TechProSecurity.com | 866-573-8878

4K Ultra HD SIP2 series NVRs

ELI-SIP2-NVR16

Model	ELI-SIP2-NVR16
System	
Main Processor	Dual-core embedded processor
Operating System	Embedded LINUX
Video & Audio	
IP Camera Input	16 channel
Two-way Talk	1channel Input, 1channel Output, RCA
Display	
Interface	2 HDMI , 1 VGA
Resolution	3840× 2160, 1920× 1080, 1280× 1024, 1280× 720, 1024× 768
Display Split	1/4/8/9/16
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording
Recording	
Compression	H.265/H.264/MJPEG
Resolution	12Mp, 8Mp, 6Mp, 5Mp, 3Mp, 1080P, 1.3Mp, 720P & etc.
Record Rate	192Mbps
Bit Rate	1~ 20Mbps
Record Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Video Detection & Alarm	
Trigger Events	Recording, PTZ, Tour, Alarm out, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips
Video Detection	Motion Detection, MD Zones: 396(22× 18), Video Loss & Camera Blank
Alarm Input	16 channel
Relay Output	6 channel

Model	ELI-SIP2-NVR16
Playback & Backup	
Playback	1/4/9/16
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device/Network/Internal SATA burner/eSATA Device
Network	
Ethernet	1 RJ-45 port (10/100/1000Mbps)
Network Function	
	HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search
Max. User Access	128 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Storage	
Internal HDD	4 SATA III ports, up to 24TB
External HDD	1 eSATA port
Auxiliary Interface	
USB	3 ports (2 Rear USB3.0, 1 Front USB2.0)
RS232	1 port, For PC communication& Keyboard
RS485	1 port, For PTZ control
General	
Power Supply	Single, AC 100~240V, 50/60 Hz
Power Consumption	17W for normal model(without HDD)
Working Environment	-10°C~+55°C/10%~90%RH/86~106kpa
Dimension (W×D× H)	1.5U, 440mm×405mm×76mm
Weight	9.6lbs (4.35KG)

*Design and specifications are subject to change without notice.



TechProSecurity.com | 866-573-8878