

HDOB-AL2IR28

Specifications

2 MP HD Bullet Camera



Features

- Megapixels: 2MP
- Max Resolution: 1080p
- Image Sensor: 2MP CMOS Image Sensor
- Minimum Illumination: 0.01 Lux @ (F1.2,AGC ON), 0 Lux with IR
- LEDs: 24
- OSD: Yes
- HD-CVI, HD-TVI, AHD and Analog

Specification

HDOB-AL2IR28

Image Sensor:	2MP CMOS Image Sensor
Signal System:	PAL NTSC
Effective Pixels:	1930(H) × 1088(V)
Min. Illumination:	0.01 Lux @ (F1.2,AGC ON), 0 Lux with IR
Shutter Time:	1/25(1/30) s to 1/50,000 s
Lens:	2.8mm
Lens Mount:	M12
Adjustment Range:	Pan: 0 - 360°, Tilt: 0 - 75°, Rotation: 0 - 360°
Day& Night:	IR cut filter with auto switch
Video Frame Rate:	PAL: 1080p@25fp NTSC: 1080p@30fps
HD Video Output:	AHD TVI CVI CVBS Output
Synchronization:	Internal Synchronization
S/N Ratio:	More than 62 dB
Up the Coax:	Support
Operating Conditions:	-20 °C - 60 °C (-20 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply:	12 VDC±15%
Power Consumption:	Max. 4W
IR Range:	Up to 20 m
Dimension:	155.5(W) x 72.5(H) x 71(D) mm
Weight:	650g