

HDOD-AL2IRZW

Specifications

2 MP HD Dome Camera



Features

- Megapixels: 2MP
- Max Resolution: 1080p
- Image Sensor: 1/2.7 inch CMOS Image Sensor
- Minimum Illumination: Color:0.1lux.BW:0.5lux.
- LEDs: 24
- OSD: Yes

Mounting Accessories



WM-SB204



JB-SB302

Specification

HDOD-AL2IRZW

Image Sensor:	2MP CMOS Image Sensor
Signal System:	PAL NTSC
Effective Pixels:	1930(H) × 1088(V)
Min. Illumination:	0.01 Lux @ (F1.2,AGC ON), 0 Lux with IR
Shutter Time:	1/25(1/30) s to 1/50,000 s
Lens:	2.8-12 mm @ F1.4, Angle of view: 35.1°- 114.5°
Lens Mount:	M12
Adjustment Range:	Pan: 0 - 360°, Tilt: 0 - 75°, Rotation: 0 - 360°
Day& Night:	IR cut filter with auto switch
Video Frame Rate:	PAL: 1080p@25fp NTSC: 1080p@30fps
HD Video Output:	AHD TVI CVI CVBS Output
Synchronization:	Internal Synchronization
S/N Ratio:	More than 62 dB
Up the Coax:	Support
Operating Conditions:	-20 °C - 60 °C (-20 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply:	12 VDC±15%
Power Consumption:	Max. 4W
IR Range:	Up to 30m
Dimension:	∅131 x 93(H) mm
Weight:	900g