

HDPTZ-AL2IR18XME

Specifications

2 MP HD PTZ Camera



Features

- Megapixels: 2MP
- Max Resolution: 1080p
- Image Sensor: 2MP Progressive Scan CMOS
- Minimum Illumination: 0 Lux (with IRs ON)
- OSD: Yes
- HD-CVI, HD-TVI, AHD and Analog

Specification

HDPTZ-AL2IR18XME

Camera	
Image Sensor:	2MP Progressive Scan CMOS
Effective Pixels:	1920(H)x1080(V)
Signal System:	PAL/NTSC
Focal Length:	5-90MM, 18X
Signal Transfer:	AHD/CVI/TVI/CVBS Selectable
Pan & Tilt	
Rotation Range:	Pan: 360°, Vertical 90°, Auto Flip 180
Rotation Speed:	Manual Speed 80°/s
Preset points:	256pcs preset (Dwell time 01-60 interval)
Guard Tours:	4 Groups (Each 16 preset dwell time and speed selectable)
AB scan range:	Any point in pan range: 0°~360°
AB scan speed:	1-9 grades
Infrared	
IR Distance:	80m
LEDs:	10pcs IR LED
Support Ambient Light Detection:	IR illumination on 1-9 selectable
General	
RS-485 Protocols:	Pelco-P, Pelco-D
Menu Language:	English
Power Supply:	12V DC
Power Consumption:	≤ 10W
Lightning Protection:	Transient voltage 6000V
Working Temperature:	-15° C ~ 60° C
Dimensions:	38.5 x 38.5 x 30.5 cm
Weight (approx):	3.5KG