

IPOB-EL2IRE

2MP IP Network Indoor/Outdoor IR Bullet Security Camera

- 1/3 inch progressive scan CMOS
- H.264&MJPEG dual-stream encoding
- Max 30fps@1080P
- Day/Night(ICR), 2DNR,AWB,AGC,BLC
- 3.6mm fixed lens
- Max. IR LEDs Length 50 Feet
- IP66, DC12V, PoE



Megapixels:	2MP
Max Resolution:	1080p
Image Resolutions:	2MP (1920x1080) / 1.3M (1280x960) / 720P (1280x720) / D1 (704x576/704x480)
Image Sensor:	1/3 Inch CMOS
Min Illumination:	Color: 0. 1Lux/F1.6; 0Lux/F1.6 (IR on)
LEDs:	30
IR Distance:	50 Feet
OSD:	Yes
Protocol:	Private/ONVIF
Operating Temperature	-22F to +140
Dimension:	2.75in x 2.6in x 6.1 in
Power:	12v DC PoE (802.3af)

Technical Specifications

Camera		
Image Sensor		1/3" progressive scan CMOS
Scanning System		Progressive
Electronic Shutter Speed		Auto/Manual 1/3(4)~1/10000
Min. Illumination		Color: 0. 1Lux/F1.6; 0Lux/F1.6 (IR on)
S/N Ratio		More than 50dB
Video Output		N/A
Camera Features		
Max. IR LEDs Length		30m
Day/Night		Auto(ICR) / Color / B/W
Backlight Compensation		BLC /HLC /DWDR
White Balance		Auto/Manual
Gain Control		Auto/Manual
Noise Reduction		2D
Privacy Masking		Up to 4 areas
Lens		
Focal Length		3.6mm (6mm optional)
Max Aperture		F1.6(F1.6)
Focus Control		Manual
Angle of View		H: 71.9°/45.3°
Lens Type		Fixed lens
Mount Type		Board-in Type
Video		
Compression		H.264H/H.264B/H.264/ MJPEG
Resolution		1080P(1920×1080)/720P(1280×720)/D1(704×576/704×480) /CIF(352×288/352×240)
Frame Rate	Main Stream	1080P(30fps)
	Sub Stream	D1/CIF(30fps)
Bit Rate		H.264H: 16K ~ 8192Kbps
Audio		
Compression		N/A
Interface		N/A
Network		
Ethernet		RJ-45 (10/100Base-T)
Wi-Fi		N/A
Protocol		IPv4/IPv6, HTTP, HTTPS, TCP/IP, UDP, UPnP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS
Compatibility		ONVIF, CGI
Max. User Access		20 users
Smart Phone		iPhone, iPad, Android, Windows Phone

Auxiliary Interface	
Memory Slot	N/A
RS485	N/A
Alarm	N/A
PIR Sensor Range	N/A
General	
Power Supply	DC12V, PoE (802.3af)
Power Consumption	Max 4W
Working Environment	-30°C~+60°C, Less than 95%RH
Ingress Protection	IP66
Vandal Resistance	N/A
Dimensions	Φ70mm×66mm×155mm
Weight	0.42Kg

Dimensions (mm)

