

IPOB-EL2IREAW

2Megapixel Full HD Cube Network Camera



- 1/3" 2Megapixel progressive scan CMOS
- H.264 & MJPEG dual-stream encoding
- Max 25/30fps@1080P(1920×1080)
- DWDR, Day/Night, 3DNR, Auto iris, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- 3.6mm fixed lens
- White LEDs length 10m
- PIR sensor range 6m
- Micro SD memory (K200A only), PoE (K200/200A), Wi-Fi (K200W only)

Technical Specifications

Camera	
Image Sensor	1/3" 2Megapixel progressive scan CMOS
Effective Pixels	1920(H)×1080(V)
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual, 1/3(4)~1/100000
Min. Illumination	0.05lux/F1.8(color)
S/N Ratio	More than 50dB
Video Output	N/A
Camera Features	
Max. LEDs Length	10m
Day/Night	Auto(Electronic) / Color / B/W
Backlight Compensation	BLC / HLC / DWDR
White Balance	Auto/Manual
Gain Control	Auto/Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas
Lens	
Focal Length	3.6mm
Max Aperture	F1.8
Focus Control	Manual
Angle of View	86.5°
Lens Type	Fixed Lens
Mount Type	Board-in Type

Video		
Compression		H.264/MJPEG
Resolution		1080P(1920x1080)/720P(1280x720)/D1/CIF
Frame Rate	Main Stream	1080P/720P(1~25/30fps)
	Sub Stream	D1/CIF(1 ~ 25/30fps)
Bit Rate		H.264: 16K ~ 8192Kbps
Audio		
Compression		G.711a / G.711u / PCM
Interface		Built-in Mic, Built-in speaker
Network		
Ethernet		RJ-45 (10/100Base-T)
Wi-Fi		Wi-Fi(802.11b/g)
Protocol		IPv4/IPv6, HTTP, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP,NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
ONVIF		ONVIF Profile S
Max. User Access		10 users
Smart Phone		iPhone, iPad, Android, Windows Phone
Auxiliary Interface		
Memory Slot		N/A
RS485		N/A
Alarm		1/1 channel In/Out
PIR Sensor Range		Up to 6m
General		
Power Supply		DC12V
Power Consumption		<5W
Working Environment		-20°C~+50°C, Less than 95%RH
Ingress Protection		N/A
Vandal Resistance		N/A
Dimensions(W×D×H)		66.6mm×99.5mm×131.2mm
Weight		0.35Kg (0.4kg with bracket)

Dimensions (mm)

