

IPOB-EL2IREW

2Mp Network IP WIFI Wireless IR Bullet Security Camera

- Wi-Fi support
- 3.6mm fixed lens
- Max. IR LEDs Length 100 feet
- Max 25/30fps@1080P(1920×1080)



Megapixels:	2MP
Image Resolutions:	1080P(1920× 1080)/720P(1280× 720)/D1(704× 576/704× 480) /CIF(352× 288/352× 240)
Image Sensor:	1/3" 2Megapixel progressive scan CMOS
Min Illumination:	Color: 0. 1Lux/F1.6; 0Lux/F1.6 (IR on)
LEDs:	N/A
IR Distance:	100 feet
OSD:	N/A
Protocol:	ONVIF, CGI
Operating Temperature	+14°F to +122°F
Dimension:	7in x 3in x 3in
Power:	DC12V

IPOB-EL2IREW

2MP Full HD Wi-Fi Network Small IR Bullet Camera

Model		IPOB-EL2IREW
Camera		
Image Sensor		1/3" 3Megapixel progressive scan CMOS
Effective Pixels		2048(H)x1536(V)
Scanning System		Progressive
Electronic Shutter Speed		Auto/Manual 1/3(4)~1/10000
Min. Illumination		Color: 0. 1Lux/F1.6; 0Lux/F1.6 (IR on)
S/N Ratio		More than 50dB
Video Output		N/A
Camera Features		
Max. IR LEDs Length		30m
Day/Night		Auto(ICR) / Color / B/W
Backlight Compensation		BLC /HLC /DWDR
White Balance		Auto/Manual
Gain Control		Auto/Manual
Noise Reduction		2D
Privacy Masking		Up to 4 areas
Lens		
Focal Length		3.6mm (6mm optional)
Max Aperture		F1.8(F1.6)
Focus Control		Manual
Angle of View		H: 72°(44°)
Lens Type		Fixed lens
Mount Type		Board-in Type
Video		
Compression		H.264H/H.264B/H.264/ MJPEG
Resolution		1080P(1920×1080)/720P(1280×720)/D1(704×576/704×480) /CIF(352×288/352×240)
Frame Rate	Main Stream	1080P(1 ~ 25/30fps)
	Sub Stream	D1/CIF(1 ~ 25/30fps)
Bit Rate		H.264H: 16K ~ 8192Kbps
Audio		
Compression		N/A
Interface		N/A
Network		
Ethernet		RJ-45 (10/100Base-T)
Wi-Fi		Wi-Fi(IEEE802.11b/g/n)
Wi-Fi Range		50m(open field)
Protocol		IPv4/IPv6, HTTP, HTTPS, TCP/IP, UDP, UPnP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS
Compatibility		ONVIF, CGI
Max. User Access		20 users

IPOB-EL2IREW

Smart Phone	iPhone, iPad, Android, Windows Phone
Auxiliary Interface	
Memory Slot	N/A
RS485	N/A
Alarm	N/A
PIR Sensor Range	N/A
General	
Power Supply	DC12V
Power Consumption	<7W
Working Environment	-30°C~+50°C, Less than 95%RH
Ingress Protection	IP66
Vandal Resistance	N/A
Dimensions	Φ70mm×66mm×155mm
Weight	0.42Kg

Dimensions (mm)

