

IPOB-SB2IRV

Specifications


2MP IP Varifocal Bullet Camera



Features

- 2MP (1920 x 1080) full real time coding
- Max. resolution: 1920 x 1080
- ICR auto switch, true day / night
- 20 ~ 30m IR night view distance
- 3D DNR, digital WDR, ROI coding
- PoE power supply
- Support smart phone, iPad, remote monitoring
- IP66 ingress protection
- Support three streams

Dimensions



Mounting Accessories



JB-SB301

Specifications

IPOB-SB2IRV

Camera	
Image Sensor	1 / 2.8 "CMOS
Image Size	1920 x 1080
Electronic Shutter	1 / 25 s ~ 1 / 100000 s
Auto Iris	Fixed Iris
Min. Illumination	0.005 lux @F1.6, AGC ON; 0 lux with IR
Lens	2.8 ~ 12 mm @ F1.4, horizontal field of view : 95.4° ~ 34.1°
Lens Mount	M12 and Φ14 optional
Day & Night	ICR
Wide Dynamic Range	
Digital NR	3D DNR
Angle Adjustment	Any angle
Image	
Video Compression	H.264 / MJPEG
H.264 Compression	Baseline Profile / Main Profile / High Profile
Standard Resolution	1080P (1920 x 1080), 720P (1280 x 720), D1, CIF, 480 x 240
Main Stream	60Hz : 1080P (1 ~ 30fps) / 720P (1 ~ 30fps) 50Hz : 1080P (1 ~ 25fps) / 720P (1 ~ 25fps)
Bit Rate	128Kbps ~ 6Mbps
Encode Mode	VBR / CBR
Quality	Five levels under VBR; Freely adjustable under CBR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc. adjustable through client software or web browser
ROI	Yes
Interfaces	
Network	RJ45
Functions	
Remote Monitoring	IE browsing, CMS remote control
Online Connection	Support simultaneous monitoring for up to 3 users ; Support multi-stream real time transmission
Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, DDNS, SMTP, FTP
Interface Protocol	ONVIF
Storage	Network remote storage
Smart Alarm	Motion alarm
PoE	Yes
IR Distance	20 ~ 30 m
Water-proof	IP66
Others	
Power Supply	DC 12V / PoE
Power Consumption	< 6.5W
Operating Environment	- 20°C ~ 50°C, 10% ~ 90% relative humidity
Dimensions (mm)	Φ87 × 219
Weight (net)	583g
Installation	Wall mounting, ceiling mounting