

IPOD-PR2EXIRE28

2MP Prime HD Network EXIR Turret Camera

- Up to 2 megapixel (1920 × 1080) resolution
- 2mm Fixed lens
- EXIR Infrared LEDs, 98 feet IR range
- 12V DC & PoE(802.3af)



Megapixels:	2
Image Resolutions:	2MP (1920x1080) / 1.3M (1280x960) / 720P (1280x720) / D1 (704x576/704x480)
Image Sensor:	1/2.8 in Progressive Scan CMOS
Min Illumination:	0.028Lux @ (F2.0, AGC ON) ,0 Lux with IR
LEDs:	N/A
IR Distance:	98 feet
OSD:	N/A
Protocol:	ONVIF
Operating Temperature	14°F - 140 °F, Humidity 95% or less (non-condensing)
Dimension:	5in x 5in x 3.83in
Power:	12 V DC Â± 10% , PoE (802.3af)



IPOD-PR2EXIRE28

2 MP HD Network EXIR Turrent Camera

Model Parameter	IPOD-PR2EXIRE28
	2 Megapixel EXIR CMOS Network Dome Camera
Camera	
Image Sensor	1/2.8" Progressive Scan CMOS
Min. Illumination	0.01Lux @ (F1.2, AGC ON) ,0 Lux with IR 0.028Lux @ (F2.0, AGC ON) ,0 Lux with IR
Shutter Speed	1/3 s to 1/100,000 s
Lens	2.8mm
Day &Night	IR cut filter with auto switch
Digital Noise Reduction	3D DNR
Wide Dynamic Range	Digital WDR
Angle Adjustment	Pan:0° - 360°, Tilt: 0° - 75°, Rotation: 0° - 360°
Compression Standard	
Video Compression	H.264/ MJPEG
H.264 Type	BaseLine Profile/Main Profile
Video Bit Rate	32 Kbps – 8 Mbps
Dual Stream	Yes
Image	
Max. Resolution	1920 × 1080
Frame Rate	50 Hz: 25 fps (1920 × 1080), 25 fps (1280 × 960), 25 fps (1280 x 720) 60 Hz: 30 fps (1920 × 1080), 30fps (1280 × 960), 30 fps (1280 x 720)
Image Settings	Rotate mode, Saturation, 720) Brightness, Contrast adjustable by client software or web browser
Backlight compensatio	Yes, zone optional
ROI	Support
Network	
Network Storage	NAS (Support NFS, SMB/CIFS)
Alarm Trigger	Intrusion detection, Line crossing detection, Motion detection, Dynamic analysis, Tampering alarm, Network disconnect , IP address conflict, Storage exception
Protocols	TCP/ IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,
General	PPPoE,NTP,UPnP,SMTP,SNMP,IGMP,802.1X,QoS,IPvFlash-prevention, dual stream, heartbeat, mirror, 6password ,Bonjour
Standard	ONVIF, PSI, CGIA
Interface	
Communication Interface	1 RJ45 10M/100M Ethernet interface

IPOD-PR2EXIRE28

2 MP HD Network EXIR Turret Camera

General	
Operating Conditions	-30 °C – 60 °C (14 °F – 140 °F) Humidity 95% or less (non-condensing)
Power Supply	12 V DC ± 10%
	PoE (802.3af)
Power Consumption	Max. 5.5 W
Ingress Protection level	IP66
EXIR Range	Approx. 20 to 30 meters
Dimensions	Φ126.7×97.21
Weight	570g

Dimensions

