

IPVD-EL3IRE

3MP HD Network Mini IR Dome Camera

- 1/3" 3Megapixel progressive scan CMOS
- Max 20fps@3MP and 25/30fps@1080P
- 3.6mm fixed lens
- IP67 weather proof IK10 vandal proof



Megapixels:	3MP
Image Resolutions:	3MP (2048x1536) / 2MP (1920x1080) / 1.3M (1280x960) / 720P (1280x720) / D1 (704x576/704x480)
Image Sensor:	1/3" 3Megapixel progressive scan CMOS
Min Illumination:	0.1Lux/F2.0(Color), 0Lux/F2.0(IR on)
LEDs:	22
IR Distance:	100 feet
OSD:	N/A
Protocol:	ONVIF
Operating Temperature	-22°F to +140°F
Dimension:	5in x 5in x 3in
Power:	DC12V, PoE (802.3af)

IPVD-EL3IRE

Technical Specifications

Model		IPVD-EL3IRE	
Camera			
Image Sensor		1/3" 3Megapixel progressive scan CMOS	
Effective Pixels		2304(H) x1536(V)	
Scanning System		Progressive	
Electronic Shutter Speed		Auto/Manual, 1s~1/100000s	
Min. Illumination		0. 1Lux/F2.0(Color), 0Lux/F2.0(IR on)	
S/N Ratio		More than 50dB	
Video Output		N/A	
Camera Features			
Max. IR LEDs Length		30m	
Day/Night		Auto(ICR)/Color/B/W	
Backlight Compensation		BLC / HLC / DWDR	
White Balance		Auto/Manual	
Gain Control		Auto/Manual	
Noise Reduction		3D	
Privacy Masking		Up to 4 areas	
Lens			
Focal Length		3.6mm	
Max Aperture		F2.0(F2.0)	
Focus Control		Manual	
Angle of View		H: 81°(92°)	
Lens Type		Fixed lens	
Mount Type		Board-in Type	
Video			
Compression		H.264/ H.264H/ H.264B/ MJPEG	
Resolution		3M(2048×1536)(2304×1296)/1080P(1920×1080)/720P(1280×720) / D1(704×576/704×480) /CIF(352×288/352×240)	
Frame Rate	Main Stream	3M(1 ~ 20fps)/1080P(1 ~ 25/30fps)	
	Sub Stream	D1(1 ~ 25/30fps)	
Bit Rate		H.264: 4kbps~8192kbps	
Corridor Mode		Support	
Audio			
Compression		N/A	
Interface		N/A	
Network			
Ethernet		RJ-45 (10/100Base-T)	
Wi-Fi		N/A	
Protocol		IPv4/IPv6, HTTP, HTTPS, TCP/IP, UDP, UPnP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS	
Compatibility		ONVIF, CGI	
Max. User Access		20 users	

IPVD-EL3IRE

Smart Phone	iPhone, iPad, Android, Windows Phone
Auxiliary Interface	
Memory Slot	N/A
RS485	N/A
Alarm	N/A
PIR Sensor Range	N/A
General	
Power Supply	DC12V, PoE (802.3af)
Power Consumption	<4W(IR on)
Working Environment	-30°C~+60°C, Less than 95% RH
Ingress Protection	IP67
Vandal Resistance	IK10
Dimensions	Φ110mm×81mm
Weight	0.47kg

Dimensions (mm)

