

IPVD-PR2IREV

Prime 2MP IP Network Vandal Proof Varifocal IR Dome Camera

- 2.8-12mm vari-focal lens
- Up to 98 feet IR distance
- 3 axis adjustable
- IK10 Vandal Proof



Megapixels:	2
Image Resolutions:	1080P(1920× 1080)/720P(1280× 720)/D1(704× 576/704× 480)/ CIF(352× 288/352× 240)
Image Sensor:	1/2.8in progressive scan CMOS
Min Illumination:	0.01 lux @F1.2, AGC ON, 0 lux with IR, 0.014 lux @F1.4, AGC ON, 0 lux with IR
LEDs:	24
IR Distance:	98 feet
OSD:	N/A
Protocol:	ONVIF, PSIA, CGI, ISAPI
Operating Temperature	-22°F ~ 140 °F, Humidity 95% or less (non-condensing)
Dimension:	5.6in x 5.6in x 3.94in
Power:	12 VDC ± 10% , PoE (802.3af)



IPVD-PR2IREV

Vandal Proof IR Dome Network Camera

IPVD-PR2IREV	
Camera	
Image sensor	1/2.8" progressive scan CMOS
Min. illumination	0.01 lux @F1.2, AGC ON, 0 lux with IR, 0.014 lux @F1.4, AGC ON, 0 lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	2.8 ~ 12 mm @F1.4, angle of view: 113° ~ 33.8°
Lens mount	Φ14
Auto iris	DC drive
Day & night	ICR
Digital noise reduction	3D DNR
Wide dynamic range	Digital WDR
Angle adjustment	Pan:0° - 355°, Tilt: 0° - 75°, Rotation: 0° - 355°
Compression Standard	
Video compression	H.264 / MJPEG
H.264 codec profile	Main/Basic profile
Bit rate	32 Kbps ~ 8 Mbps
Audio compression	G.711 / G.722.1 / G.726 / MP2L2
Audio bit rate	64 Kbps (G.711) / 16Kbps (G.722.1)/ 16 Kbps (G.726) / 32-128 Kbps
Image	
Max. Image Resolution	1920 x 1080
Frame rate	50 Hz: 25 fps (1920 x 1080), 25 fps (1280 x 960), 25 fps (1280 x 720) 60 Hz: 30 fps (1920 x 1280), 30 fps (1280 x 960), 30 fps (1280 x 720)
Backlight compensation	Yes, zone configurable
Image settings	Rotate mode, Saturation, brightness, contrast, sharpness adjustable through client software or web browser
ROI	Yes
Network	
Network storage	NAS
Alarm trigger	Motion detection, tampering alarm
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
System compatibility	ONVIF, PSIA, CGI, ISAPI
General functionalities	User authentication, watermark, dual stream
Interface	
Communication interface	1 RJ45 10 M / 100 M Ethernet interface
Onboard storage	Built-in Micro SD / SDHC / SDXC card slot, up to 64 GB
General	
Operating conditions	-30 °C ~ 60 °C (-22°F ~ 140 °F) humidity 95% or less (non-condensing)
Power supply	12 VDC ± 10% , PoE (802.3af)
Power consumption	Max. 5.5W (max. 7W with ICR on)
Impact protection	Up to IK10
Ingress protection level	IP66
IR range	Up to 30m
Dimensions	Φ142 x 99.9 mm (Φ 5.6" x 3.94")
Weight	1000g

Dimensions

