

Product Specifications

NVR-ELC-16-DH

Features:

- 16ch IP camera inputs
- 1/1ch Mic in/out
- Compatible with 5MP, 3MP, 1080P, 720P, D1 and etc.
- HDMI, VGA output up to 1080P, 1 TV
- 16ch alarm in & 4ch relay out, RS485, RS232
- 4 SATA, 2 USB, 1 RJ45 (1000Mbps)



Main Processor	Dual-core embedded processor
Operating System	Embedded LINUX
IP Camera Input	16 channel
Two-way Talk	1 channel Input, 1 channel Output, BNC
Interface	1 HDMI, 1 VGA, 1TV
Display Resolution	1920×1080, 1280×1024, 1280×720, 1024×768
Display Split	1/4/8/9/16
OSD	Camera title, Time, Video loss, Camera lock, Motion detection
Compression	H.264 / MJPEG
Resolution	5MP (2560x1920) 3MP(2048×1536) 1080P(1920×1080) 720P(1280×720) D1(704×576/704×480)
Record Rate	Max 200Mbps
Bit Rate	48~ 8192kbps
Record Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec,
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Buzzer
Video Detection	Motion Detection, MD Zones: 396(22×18), Video Loss & Camera
Alarm Input	16 channel
Relay Output	4 channel
Sync Playback	1/4/9/16

