

OD-CM1200VIRW

1200 TVL Indoor-Outdoor IR Varifocal Vandal Resistant Dome

- 1200 TVL
- Varifocal 2.8-12mm Lens
- IR 100 Feet
- Vandal Resistant Dome
- Indoor/Outdoor



TV Lines:	1200
Image Resolutions:	960H / D1
Image Sensor:	CMOS
Min Illumination:	0.01Lux/F2.0
LEDs:	36
IR Distance:	100 Ft
OSD:	No
Operating Temperature	+14F to +122
Dimension:	5.2in x 5.2in x 3.7in
Power:	12v DC 700mA

Camera

CCD/CMOS	CMOS
Image Sensor	HS1200
DSP	FH8526
Horizontal Resolution	1200TVL
Effective Pixels	1296(H)X964(v)
TV System	NTSC
Electronic Shutter Time	Auto: NTSC 1/60-1/100, 000Sec
Sync System	Internal
Usable Illumination	0.01Lux/F2.0
S/N Ratio	≥44dB
Gamma Correction	0.45
Scanning System	NTSC:525 Lines, 60 Field/Sec
Video Output	Composite Signal (1.0Vp-p, 75Ω)

Lens

Focus Length	2.8-12mm
Focus Control	Manual
Lens Type	Manual
Pixels	2M Pixels
Auto Iris Support	NO

Night Vision

Infrared LED	36PCS
Infrared Distance	30M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control

Camera Features

Day/Night	Color/ B&W
OSD Menu Language	NO
Defog	NO
Sense-up	NO
Smart-IR	NO
Wide Dynamic Range	NO
Backlight Compensation	NO
White Balance	AUTO
Gain Control	AUTO
Noise Reduction	2DNR
Privacy Masking	NO
Digital Zoom	NO
Picture Adjustment	NO
UTC Support	NO

General

Vandalproof Housing	YES
Lens Angle Adjustment	YES
Dual Voltage	NO
IR Cut Filter	YES
Heater	NO
Operation Temperature	-10℃ ~ +50℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 700mA
Dimension	Ø 131 x 93(H)mm
Weight	800g