



Features

Vandalproof IR Dome Camera

SHARP Color CCD

IR LED: 5X23PCS ,IR Distance: 20M

Back Light Compensation(BLC)

Auto White Balance(AWB)

Lens: Board Lens 3.6mm/F2.0

Dimension : 94 x 68.5(H) mm



Image Sensor	1/4"SHARP
Horizontal Resolution	420 TV Line
Pixels	PAL:500(H)×582(V) NTSC:510(H)×492(V)
TV System	PAL/NTSC
IR LED	5 X 23 PCS
IR Series Distance	20 M
Lens	Board Lens 3.6mm/F2.0
Sync System	Internal
IR Status	Under 10 Lux By CDS
Usable Illumination	0 Lux/F2.0 (LED ON)
IR Power On	CDS Auto Control
S/N Ratio	≥48dB (AGC OFF)
Gamma Correction	0.45
Video Out	Composite Signal (1.0Vp-p, 75Ω)
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec
Operation Temperature	14 to 122 Fahrenheit @ RH95% Max
Storage Temperature	-4 to 140 Fahrenheit @ RH95% Max
White Balance	Auto
Power Source	DC12V 250mA
Dimension	94 x 68.5(H) mm
Weight	450G