

**Features OD-LX530IR50**

Vandalproof IR Dome Camera

1/3" Sony Super HAD CCD

530 TV Lines Resolution

IR LED:24PCS ,IR Distance: 50Ft

0 LUX at night time

3.6 mm Lens

*Dimension : 95 x 77(H) mm***Camera Specifications OD-LX530IR50**

<i>Image Sensor</i>	1/3" Sony Super HAD CCD
<i>Horizontal Resolution</i>	530 TV Line
<i>Picture Elements</i>	PAL:795(H)×569(V) 470K Pixels NTSC:811(H)×508(V) 410K Pixels
<i>Effective picture Elements</i>	PAL:752(H)×582(V) 440K Pixels NTSC:768(H)×494(V) 380K Pixels
<i>Scanning area</i>	2:1 Interlance (NTSC) 525 Lines/60 Fiels/30 Frames 2:1 Interlance (PAL) 625 Lines/50 Fiels/25 Frames
<i>Lens</i>	3.6 mm Fixed Lens
<i>Minimum Illumination</i>	0 Lux at IR ON
<i>Video Output</i>	1.0 Vp-p (NTSC) / 1.0 Vp-p (PAL)
<i>Electronic IRIS</i>	1/60-1/120,000 sec (NTSC) / 1/50-1/120,000 sec (PAL)
<i>Back Light Compensation</i>	Build-In
<i>IRIS Mode</i>	ESC
<i>AGC</i>	Build-In
<i>White Balance</i>	Auto
<i>LED</i>	24 LEDs
<i>Gamma</i>	r=0.45
<i>S/N Ratio</i>	48dB (AGC OFF)
<i>Dimension</i>	95(W) x 95(L) x 77(H) mm
<i>Operating Temp.</i>	-4' C to 50' C
<i>Power Source</i>	DC12V / 300mA
<i>Weight</i>	1Lbs
<i>Power Source</i>	DC12V / 300mA