

Product Specifications

OD-LX600IR50-W



The OD-LX600IR50-W is an extremely versatile security camera. This camera features a brand new Easy-Mount design in a white case that will blend in with most environments. It features a 1/3" inch CCD with a 3.6mm lens. This security camera can be mounted indoors or outdoors, is weatherproof and can withstand almost any temperature. With 600tvl and a 3.6mm lens you can expect outstanding and detailed overviews. This is a great value for an overview camera that does not need a complicated OSD to configure the settings. If you are looking for a security camera with OSD and WDR, please check out our new OD-LX650IR50-W. At night, the Infrared LEDs will turn on automatically and will provide up to 60'ft of IR illumination in complete darkness, more if there is just a little bit of light. You can easily wall or ceiling mount this security camera. We find ourselves using this security camera more than any other. Since it weighs less than one pound, they are easy to mount to drop ceiling panels as well.

IMAGE SENSOR:	1/3" CCD
HORIZONTAL RESOLUTION:	600 TV Lines, Low Illumination
TV SYSTEM:	NTSC or PAL
SYNC SYSTEM:	Internal Synchronization
LENS:	Board Lens 3.6mm / F2.0
LED:	24pcs x Diameter 5 LED, 20m IR Range
MINIMUM ILLUMINATION:	0.001Lux/F2.0 - (0 Lux With IR On)
SYNCHRONOUS SYSTEM:	Internal Negative Sync.
S/N RATIO:	≥52dB (AGC OFF)
SCANNING SYSTEM:	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec
ELECTRONIC SHUTTER TIMES:	Auto:PAL 1/50-1/100, 000Sec;NTSC 1/60-1/100, 000Sec
GAMMA CORRECTION:	0.45
VIDEO OUTPUT:	Composite Signal 1.0 Vp-p, 75 Ohms
WHITE BALANCE:	Auto
VOLTAGE:	12VDC (+/-10%)
CURRENT:	150mA
DIMENSION:	Diameter 94 x 69(H)mm
WEIGHT:	400g
OPERATION TEMPERATURE:	-10°C - +50°C (RH95% Max)
COLOR:	White