


PENDVR-PRE4ME

Prime 4 Channel 2MP Pentabrid CVI/TVI/CCTV/AHD/IP 1U Recorder

- Can do H.265/H.265+ on both IP & Analog
- Supports real-time 1080p lite
- HDMI output at up to 4K
- Up to 1-ch 4MP IP camera input
- Self-adaptive HDTV/HD-CVI/AHD/CVBS signal input



Recording Speed:	3MP / 1080p / 720p / D1 Max 6 Mbps
Resolution:	3MP/1080p/1080p lite/720p/720p lite/VGA/WD1/4CIF/CIF
Drive Capacity:	1 SATA
Video Inputs:	4
Ethernet Ports:	1
Video Outputs:	VGA / BNC / HDMI
Audio Inputs:	1
Audio Outputs:	1
Alarm Inputs:	No
Alarm Outputs:	No
Internal DVD Burner Support:	No
Smart Phone Access/Push Notification	Yes
Motion Activated Recording:	Yes
PTZ Control:	Yes
Simultaneous Remote Users:	128



PENDVR-PRE4ME


4 Channel 2MP Pentabrid CVI/TVI/CCTV/AHD/IP 1U Recorder

Model		PENDVR-PRE4ME
Video/Audio input	Video compression	H.265+/H.265/H.264+/H.264
	Analog video input	4-ch BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection
	HDTVI input	3 MP, 1080p30, 1080p25, 720p60, 720p50, 720p30, 720p25 Note: The 3 MP signal input is only available for channel 1 of PENDVR-PRE4ME
	AHD input	1080p25, 1080p30, 720p25, 720p30
	HDCVI input	1080p25, 1080p30, 720p25, 720p30
	CVBS input	PAL/NTSC
	IP video input	1-ch Up to 4 MP resolution Supports H.265+/H.265/H.264+/H.264 IP cameras
	Audio compression	G.711u
	Audio input	1-ch, RCA (2.0 Vp-p, 1 KΩ)
Video/Audio output	CVBS output	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480
	HDMI/VGA output	1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
	Encoding resolution	When 1080p Lite mode not enabled: 3 MP/1080p/720p/VGA/WD1/4CIF/CIF; When 1080p Lite mode enabled: 3 MP/1080p lite/720p lite/VGA/WD1/4CIF/CIF
	Frame rate	Main stream: When 1080p Lite mode not enabled: For 3 MP stream access: 3 MP/1080p/720p/VGA/WD1/4CIF/CIF@15fps For 1080p stream access: 1080p/720p@15fps; VGA/WD1/4CIF/CIF@25fps (P)/30fps (N) For 720p stream access: 720p/VGA/WD1/4CIF/CIF@25fps (P)/30fps (N) When 1080p Lite mode enabled: 3 MP@15fps 1080p lite/720p lite/VGA/WD1/4CIF/CIF@25fps (P)/30fps (N) Sub-stream: WD1/4CIF@12fps; CIF@25fps (P)/30fps (N)
	Video bit rate	32 Kbps to 6 Mbps
	Audio output	1-ch, RCA (Linear, 1 KΩ)
	Audio bit rate	64 Kbps
	Dual stream	Support
	Stream type	Video, Video & Audio
	Synchronous playback	4-ch
Network management	Remote connections	128
	Network protocols	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF
Hard disk	SATA	1 SATA interfaces
	Capacity	Up to 6 TB capacity for each disk
External interface	Two-way audio input	1-ch, RCA (2.0 Vp-p, 1 KΩ) (using the 1 st audio input)
	Network interface	1, RJ45 10M/100M self-adaptive Ethernet interface
	USB interface	2 × USB 2.0
	Serial interface	RS-485 (half-duplex)
General	Power supply	12 VDC
	Consumption (without HDD)	≤ 6 W
	Working temperature	-10 °C to +55 °C (+14 °F to +131 °F)
	Working humidity	10% to 90%
	Dimensions (W × D × H)	315 × 242 × 45 mm (12.4 × 9.5 × 1.8 inch)
	Weight (without HDD)	≤ 1.16 kg (2.6 lb)

PENDVR-PRE4ME

4 Channel 2MP Pentabrid CVI/TVI/CCTV/AHD/IP 1U Recorder

Physical Interfaces



NOTE The rear panel of AR324-4/324-8 provides 4/8 video input interfaces.

Index	Description	Index	Description
1	VIDEO IN	7	LAN Network Interface
2	AUDIO IN, RCA Connector	8	RS-485 Serial Interface
3	AUDIO OUT, RCA Connector	9	12 VDC Power Input
4	VGA Interface	10	Power Switch
5	HDMI Interface	11	GND
6	USB Interface	12	VIDEO OUT