

Product Specifications

PTZ-LX570L10X



The PTZ-LX570L10X is our best value in Pan-Tilt-Zoom cameras. Unlike most other PTZ cameras, this security camera includes both an indoor ceiling mount and an outdoor wall mount. This will save you a lot of money in accessories that you normally have to buy separately. This 10X PTZ features a Samsung module with a Sony Super HAD CCD, 2.8-38mm Lens and an ICR day/night filter. This PTZ security camera is exceptionally small so it won't stand out like a standard PTZ camera. With the built in 10X

Optical Zoom you will be able to zoom in to objects far away and they will appear up to 10 times closer than they really are. This PTZ security camera is weatherproof when mounted using the outdoor wall mount and is a very high resolution PTZ providing excellent detail from a distance. Additionally, this PTZ can be programmed to scan or follow preset patterns from the DVR using presets or using the PTZ programming tool which is sold separately. You can also use the PTZ tool to pan-tilt-zoom the camera without having access to the DVR. This PTZ security camera is recommended for inside office spaces, or small parking lots and it can take the place of several security cameras.

MODEL:	PTZ-LX570L10X
IMAGE SENSOR:	SAMSUNG 10X SDM-100, 1/4" Super HAD Color CCD, ICR, 10X(f=3.8~38mm)
HORIZONTAL RESOLUTION:	Color 500TVL, Black 570TVL
PIXELS:	PAL:795 (H)× 596(V) NTSC :811 (H) ×508 (V)
TV SYSTEM:	PAL/NTSC
LENS:	10X optical zoom lens(f=3.8~38mm)
SYNC SYSTEM:	Internal
USABLE ILLUMINATION:	0.001Lux/F2.0
S/N RATIO:	> / -54dB (AGC OFF)

Product Specifications

GAMMA CORRECTION:	0.45
VIDEO OUT:	Composite Signal (1.0Vp-p, 75Ω)
SCANNING SYSTEM:	PAL:625 Lines, 50 Field/Sec; NTSC:525 Lines, 60 Field/Sec
ELECTRONIC SHUTTER TIME:	Auto:PAL 1/50-1/100,000Sec; NTSC 1/60-1/100,000Sec
OPERATION TEMPERATURE:	-10C ~ +50C RH95% Max
STORAGE TEMPERATURE:	-20C ~ +60C RH95% Max
WHITE BALANCE:	Auto
POWER SOURCE:	DC12V 700mA
DIMENSION:	138x212mm
WEIGHT:	2800g