

Product Specifications

PTZ-LX650L3X



The PTZ-LX650L3X offers an affordable PTZ solution to enhance and expand the view of your surveillance system. This security camera features the Sony Super HAD II CCD and has it's own OSD (On Screen Display) which will allow you to configure many different options including DWDR (Digital Wide Dynamic Range), Sens Up, BLC, and much, much more. With a super high 650TVL resolution and a built-in 5-15mm 3x zoom lens, this camera will satisfy most, if not all, of your PTZ requirements. The

DWDR setting is perfect for inside store fronts that have big entrances or windows with bright sunlight outside. It can compensate for multiple lighting environments at the same time. The Sense UP settings will enhance the night time viewing to allow for clear video in extremely low light. The high quality, weatherproof housing can be used indoors or outdoors and comes standard with a wall and a ceiling mount for even greater versatility and value.

MODEL:	PTZ-LX650L3X
DOME TYPE:	4" Indoor/Outdoor PTZ dome, ABS case
PROTOCOL:	Pelco-P/D
BAUD RATE:	1200/2400/4800/9600 bps
ADDRESS:	0-255
PAN ROTATION:	360 Continues rotation
TILT ROTATION:	0 ~ 90 Flip
MAX PAN SPEED:	60/Sec
MAX TILT SPEED:	30/Sec
PRESET SPEED:	100/Sec
PRESET ACCURACY:	+/- 32 Points
PRESET POINTS:	32 Points

Product Specifications

PATTERN TOURS:	Programmable 16 preset point Programmable preset point number and dwell time / speed
AUTO SCAN:	Yes (Programmable speed and left right limited point)
POWER-OFF MEMORY:	Current setting and state (Including Pattern, Not including auto scan)
HOME POSITION:	Yes (Programmable auto return to home position)
ZOOM:	Optical 3X (5-15mm)
PROTECTION:	IP66 for outdoor use (Wall Mount)
OPERATING:	-5C ~ 60C
POWER:	12VDC 500mA
COMMUNICATION:	RS485 (+/-)