

PWR-8

8 Channel Power Distribution Box



- Input: 110/120V AC
- Output: 12V DC per channel
- Supply Current: 4 Amp
- Max Amp: 0.65 Amp per channel
- Integral Surge Protection
- Individual LED Power Indication

Weight	1.00kg	
Input	Input Voltage	110/120VAC
	Input Voltage Frequency	60Hz
	Average Input Current	100Vac $\leq$ 4.0A
	Efficiency	$\geq$ 80%
Output	Output Voltage	12VDC $\pm$ 5%
	Output Current	4A, 8channels for 8 sets load
	Output Ripple Noise (Vp-p)	80mVp-p@25°C/ Rated input voltage & Output rated load
	reply time of starting up	$\leq$ 3S Input 100Vac, Output rated load
Fuse	Type /Rating	PTC 0.65A/60V
Protection	Over voltage protection	When over voltage occurs, it will be switch to self-protection status to protect the load.
	Over current protection	When over current occurs, the corresponding channel output will automatically switch to self-protection status, and the other channels output work normally, when clearing of fault, then switch back to normal.
	short-circuit protection	When short-circuit occurs, individual PTC fuse will break the circuit, when clearing of fault, it switch back to normal automatically.
Circumstances	Working Temperature	0°C $\sim$ +50°C
	Storage temperature	-20°C $\sim$ +80°C
	RH	20% $\sim$ 90%
	Heat release	Natural heat dissipation
Connection	Input	Three-pin socket
	Output	8channels output
Dielectric Strength	Input to output	1500Vac/60S leakage current $\leq$ 1.5ma
	Input to FG	1500Vac/60S leakage current $\leq$ 2.0ma
	FG to output	500Vac/60S leakage current $\leq$ 1.5ma
Insulating strength	Input to output	$\geq$ 20M Ω /500VDC@25°C
Leakage Current	$\leq$ 0.12ma @AC110V/25°C	
RG	$\leq$ 0.011 Ω @DC8V/25A/25°C	