



Features

- > Input 110/120 VAC
- > Output 12V DC, 9channels
- > 10Amp Supply Current
- > Integral Surge Protection
- > Individual LED Power Indication
- > Individual PTC Output Protection
- > Max. Amp: 1.6Amp/ch
- > UL Listed

PWR-9-10A-UL

Camera DC Power Supply

Specification	120W12V10A9P	
Shape Dimension	24.5×20.8×8.1cm	
Input	Input Voltage	110/120VAC
	Input Voltage Frequency	60Hz
	Average Input Current	100Vac≤1.6A
	Efficiency	≥80%
Output	Output Voltage	12VDC±5%
	Output Current	10A, 9 channels for 9 sets load
	Output Ripple Noise (Vp-p)	110mVp-p@25℃/ Rated input voltage & Output rated load
	reply time of starting up	≤3S Input 100Vac, Output rated load
Fuse	Type /Rating	PTC 1.6A/60V
Protection	Over voltage protection	When over voltage occurs, it will be switch to self-protection status to protect the load.
	Over current protection	When over current occurs, the corresponding channel output will automatically switch to self-protection status, and the other channels output work normally, when clearing of fault, then switch back to normal.
	short-circuit protection	When short-circuit occurs, individual PTC fuse will break the circuit, when clearing of fault, PTC fuse will automatically back to close.
Circumstances	Working Temperature	0℃~+50℃
	Storage temperature	-20℃~+80℃
	RH	20%~90%
	Heat release	Natural heat dissipation
Connection	Input	Three-pin socket
	Output	9channels output
Dielectric Strength	Input to output	1500Vac/60S leakage current≤1.5ma
	Input to FG	1500Vac/60S leakage current≤2.0ma
	FG to output	500Vac/60S leakage current≤1.5ma
Insulating strength	Input to output	≥20MΩ/500VDC@25℃
Leakage Current	≤0.02ma @AC110V/25℃	
RG	≤0.012Ω @DC8V/25A/25℃	