

QDVR-SBE32C: Specifications

Tribrid DVR 4 HDD CVI | TVI | AHD | 960H



Key Features:

- 32 channel BNC Outputs CVI | TVI | AHD | 960H
- 32ch 1080p / 1080p lite/ 720p /WD1 Resolutions
- Compact 4 SATA Hard Drive Bays up to 6TB each
- Intuitive and User-friendly GUI with Modular Design
- 16ch Simultaneous playback
- Recording Modes in Manual, motion, sensor or timer
- Search video: by time, calendar and events
- Express backup options
- Remote Monitoring via Browser or CMS
- Mobile Viewing Via Sibell Mobile App on IOS & Android
- NAT function & QRCode scan to set up mobile viewing

Model#: QDVR-SBE32C		
System	Compression	Standard H.264 High Profile
	CPU	Cortex A9
	OS	Embedded Linux
Video	Input	BNC × 32
	Resolution	CVI /FTVI / AHD 1080P, 720P, WD1 real time
	Output	HDMI × 1 : 1920 × 1080, VGA × 1 : 1920 × 1080, BNC × 1 : CVBS (used as the main or spot output)
Audio	Input	RCA × 4
	Output	RCA × 1
	Two-way audio	Take up channel one audio input
Record	Resolution	1080P, 1080P lite, 720P, WD1
	Frame Rate	1080P : 12 fps (PAL) / 15 fps (NTSC) 1080P lite / 720P / WD1 : 25 fps (PAL) / 30 fps (NTSC)
	Bit Rate	768Kbps ~ 8Mbps
	Mode	Manual, timer, motion, sensor
Play back	Playback	16 CH
	Search	Time slice / time / event / tag search
	Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events
	Function	Play, pause, FF, FB, digital zoom, etc.
Alarm	Mode	Manual, sensor, motion, exception
	Input	4
	Output	1
	Triggering	Record, snap, preset, e-mail, etc.
Network	Interface	RJ45 10M / 100M / 1000Mbps × 1
	Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP
	Web Client	Multiple users online
Mobile Device	OS	iOS, Andriod
Storage	HDD	SATA × 4, max 6T per HDD
Backup	Local Backup	U disk, USB removable HDD
	Network Backup	Yes
Port	RS485	RS485 × 1, connect to PTZ or keyboard
	USB	USB 2.0 × 1 (front panel), USB 3.0 × 1 (rear panel)
	Remote Controller	Yes
General	Power Supply	ATX 250W
	Consumption	≤ 20W (without HDD)
	Dimensions	440mm × 390mm × 70mm (W × D × H) 17in × 15in × 3in (W × D × H) 2U
	Work Environment	-10 ~ 50 °C , 10%- 90% humidity