



SURVEILUX®

DAY & NIGHT IR BULLET SURVEILLANCE CAMERA

SVB-42IR28L49



SPECIFICATIONS


ITEM	SVB-42IR28L49	
TV System	NTSC	PAL
Image Sensor	1/3" SONY SuperHAD CCD	
Sync. System	Internal	
Scanning System	525 Lines, 60 Fields/Sec	625 Lines, 50 Fields/Sec
Min. illumination	0.1Lux 5600 K F2.0 / 0.000Lux (IR LED On)	
Lens	4~9mm DC Auto Iris	
Resolution	420TV Lines	
S/N Ratio	48dB Min. (AGC off)	
White Balance	ATW	
WB Range	AWB, ATW (3200~10000K)	
Electrical Shutter	1/60~1/100,000sec	1/50~1/100,000sec
IR LED	28 Unit Infrared LED, 20,000hrs 850nm (Option 920nm)	
GammaCorrection	$\gamma=0.45$	
Beam Spread	36+56"	
Night View Distance	Indoor: 60m / Outdoor: 40m	
Gain Control	AGC	
Operation Temp'	-20°C~50°C	
Water Resistance	IP-55 / NEMA4	
Operational Hum'	Within 90% RH	
Power Supply	12VDC	
Cable	500mm BNC, DC Jack	



FEATURES

- 1/3" Sony SuperHAD CCD
- Day & Night
- Mirror Function(Optional)
- BLC(Back Light Compensation)
- High Resolution:Vivid Sharp Picture
- Indoor : 60m/Outdoor : 40m
- 28 Units Infrared LED
- 4~9mm DC Auto Iris Lens
- Built-in Cooling Fan
- Rainproof

DIMENSIONS



SURVEILUX®

The Art of Surveillance