



VEILUX®

3-AXIS DOME CAMERA

SVD-58L2810



SPECIFICATIONS

ITEM	SVD-58L2810
Pick Up Element	1/3" SONY
Horizontal Resolution	580 TV Lines
Effective Picture Elements (H * V)	PAL: 752 (H) x 582 (V) NTSC: 768 (H) x 494 (V)
S/N Ratio	More than 48dB
Clock Frequency (MHZ)	NTSC: 28.636, PAL: 28.375
Scanning System	2:1 Interlace
Minimum illumination	0.1 Lux
Synchronous System	Internal, Negative Sync.
Auto Electronic Shutter	NTSC: 1/60s ~ 1/100,000s PAL: 1/50s ~ 1/100,000s
Gamma Characteristic	0.45
Video Output	1.0 Vp-p, 75Ω
Auto Gain Control	Auto
Power / Current	12VDC (+/- 10%) / 120mA
Lens	2~10mm
Dimension (mm)	118 x 102
Weight (g)	300
Storage Temperature	-30°C ~ +60°C
Operation Temperature	-10°C ~ +45°C



FEATURES

- Sensor (CCD) - Adopt 1/3" High Resolution Color CCD Sensor
- Auto Gain Control (AGC) - Built-in Auto Gain Control (AGC) Circuit. The Color Camera Can Get High Definition Picture in Low Lux Condition
- Auto Electronic Shutter (AES) - Built-in Auto Electronic Shutter Function. The Color Camera's AES Speed Can Reach 1/100,000s
- Gamma Characteristic - Camera Gamma Characteristic is 0.45
- Scanning Mode - NTSC or PAL Mode



VEILUX®

The Art of Surveillance

3015 Eagle Drive, Suite 100, Grand Prairie, Texas 75052
Local Number: (214) 635-4855 / Fax: (928) 437-6270
sales@veilux.net
www.veilux.net