



VEILUX®

MINI HIGH SPEED PTZ CAMERA

SVP-54CDN10X



AGC Auto Gain Control
OFF **ON**



0.02 LUX

AWB Auto White Balance



VOLTAGE 12DC



BLC Back Light Compensation
OFF **ON**



540 TV LINES



10X ZOOM



D&N
NIGHT **DAY**



FLICKERLESS



SPECIFICATIONS

ITEM	SVP-54CDN10X	
Signal System	NTSC	PAL
Signal Formate	1/4" Inter Line Transfer CCD	
S/N Ratio	50DB (AGC Off, Weight On)	
Illumination	Color: 0.7 Lux; Black & White: 0.02 Lux	
Day & Night	Yes	
Optical Zoom	10x	
Lens	f=3.8 ~ 38mm, F 1.8 ~ 3.2	
BLC	AWC / Auto / Manual	
AGC	Auto / Manual	
Pan / Tilt Speed	Pan: 0.05 ~ 400°/sec; Tilt: 0.03 ~ 240°/sec	
Pan / Tilt Range	Pan: 0 ~ 360° Continuous; Tilt: 0 ~ 90°, Auto Flip	
Presets	256	
Auto Cruise	Auto Switch From 1 to 30 Preset Positions Sequentially	
Pattern Scan	4 Routes Of Pattern Scan	
Comm. Port	RS-485	
Baud Rate	2400bps, 4800bps, 9600bps	
Protocols	Pelco D, Peco P	
Operation Temp	-250°C ~ +70°C (w/o Heater)	
Power	12VDC	

FEATURES

- Equipped With Samsung 10X Optical Zoom
- Built-in English OSD Menu
- Auto Actions (Such as Preset, Cruise, Pattern Scan Etc.) On Power Up and Park
- Hi-Precision Motor Providing Stable and Precise Performance
- Pan / Tilt Speed Adaptive to Zoom Times
- Integrated Design with Compact Construction and High Reliability



VEILUX®
The Art of Surveillance

3015 Eagle Drive, Suite 100, Grand Prairie, Texas 75052
Local Number: (214) 635-4855 / Fax: (928) 437-6270
sales@veilux.net
www.veilux.net