



VEILUX®

OBJECT AUTO-TRACKING DOME CAMERA

SVP-AT18X



Surface



In-Ceiling



Outdoor



AWB

Auto White
Balance

1.0
LUX



BLC

Back Light
Compensation

OFF

ON

VOLTAGE

12DC



OPTICAL/
DIGITAL
ZOOM

480
TV LINES

PAN/TILT/ZOOM



SPECIFICATIONS

ITEM	SVP-AT18X	
Mounting Type	Surface, In-Ceiling, Wall, Pole	
Signal System	NTSC	PAL
Image Sensor	1/4" Sony Color CCD	
Resolution	480 TV Lines (Color)	
Pan / Tilt Speed	Pan: 0.05°~400°/sec; Tilt: 0.03°~240°/sec	
S/N Ratio	More than 50db (AGC OFF)	
Min. illumination	1.0 Lux	
Gain Control	Auto / Manual	
Back Light Comp'	Auto/Manual	
Optical Zoom	18X	
Digital Zoom	2X	
Lens	F1.4-F3.0 f=4.1-73.8mm	
Panning Range	Pan: 0°~360° ; Tilt: 0°~90°	
Preset Position No.	256	
Auto Cruise	Auto Switch from 0 to 54 preset pos' sequentially	
Pattern Scan	P/T/Z scan from 55 to 63 preset pos' automatically	
Comm. Port	RS-485	
Baud Rate	1200bps, 2400bps, 4800bps, 9600bps, 19200bps	
Spectra Address	0~255	
Power Supply	12VDC 15W	
Track Speed	0°~100° /sec	

FEATURES

- Motion Auto Tracking, Intelligent Surveillance with Alarm Function
- Preset, Auto Cruise & Pattern Scan Function
- Multi Communication Protocol Supported, Baud Rate Programmable
- 360° Continuous Pan
- 0° to 9° Tilt From Horizontal Plane Auto Flip 180°
- Iris & Focus in Manual / Auto Mode
- White Balance, Auto/ Manual
- Back Light Compensation, Auto/ Manual

MODEL NUMBERS

SVP-AT18XI	In-Ceiling
SVP-AT18X0	Outdoor
SVP-AT18XS	Surface Mount



VEILUX®
The Art of Surveillance