



VEILUX®

OBJECT AUTO-TRACKING DOME CAMERA

SVP-ATDN18X



Surface



In-Ceiling



Outdoor



AWB Auto White Balance



BLC Back Light Compensation
OFF **ON**



**OPTICAL/
DIGITAL
ZOOM**



**0.01
LUX**



VOLTAGE 12DC



**480
TV LINES**



PAN/TILT/ZOOM

SPECIFICATIONS

ITEM	SVP-ATDN18X	
Mounting Type	Surface, In-Ceiling, Wall, Pole	
Signal System	NTSC	PAL
Image Sensor	1/4" Sony Color CCD	
Resolution	480 TV Lines (Color)	
Pan / Tilt Speed	Pan: 0.05°~400°/sec; Tilt: 0.03°~240°/sec	
S/N Ratio	More than 50db (AGC OFF)	
Min. illumination	0.01 Lux	
IR Cut Filter	Yes	
Gain Control	Auto / Manual	
Back Light Comp'	Auto/Manual	
Optical Zoom	22x	
Digital Zoom	2x	
Lens	F1.6-F3.8 f=4-88mm	
Panning Range	Pan: 0°~360° Continuous ; Tilt: 0°~90°	
Preset Position No.	256	
Auto Cruise	Auto Switch from 0 to 54 preset pos' sequentially	
Pattern Scan	P/T/Z scan from 55 to 63 preset pos' automatically	
Comm. Port	RS-485	
Baud Rate	1200bps, 2400bps, 4800bps, 9600bps, 19200bps	
Spectra Address	0~255	
Power Supply	12VDC 15W	
Track Speed	0°~100°/sec	

FEATURES

- Motion Auto Tracking, Intelligent Surveillance with Alarm Function
- Preset, Auto Cruise & Pattern Scan Function
- Multi Communication Protocol Supported, Baud Rate Programmable
- 360° Continuous Pan
- 0° to 9° Tilt From Horizontal Plane Auto Flip 180°
- Iris & Focus, Auto/ Manual
- White Balance, Auto/ Manual
- Back Light Compensation, Auto/ Manual

MODEL NUMBERS

SVP-ATDN18XI	In-Ceiling
SVP-ATDN18XO	Outdoor
SVP-ATDN18XS	Surface Mount



VEILUX®
The Art of Surveillance