



SURVEILUX®

PAN-TILT-ZOOM DOME CAMERA

SVP-SDN18X



In-Ceiling



Outdoor



AWB Auto White Balance



BLC Back Light Compensation
OFF **ON**



AGC Auto Gain Control
OFF **ON**



**OPTICAL/
DIGITAL
ZOOM**



**0.1
LUX**



VOLTAGE 24AC



**480
TV LINES**



PAN/TILT/ZOOM

SPECIFICATIONS

ITEM	SVP-SDN18X	
Mounting Type	Surface, In-Ceiling	
Signal System	NTSC	PAL
Image Sensor	1/4" Sony Color CCD	
Resolution	480 TV Lines (Color)	
Pan / Tilt Speed	Pan: 0.05"~24°/sec; Tilt: 0.03~12°/sec	
S/N Ratio	More than 50db (AGC OFF)	
Min. illumination	0.01 Lux	
IR Cut Filter	Yes	
Gain Control	Auto / Manual	
Back Light Comp'	Auto/Manual	
Optical Zoom	18x	23x
Digital Zoom	2x	
Lens	F1.4-F3.0 f=4.1-73.8mm	F1.6-F3.7 f=3.6-82.8mm
Panning Range	Pan: 0°~355° ; Tilt: 0°~90°	
Preset Position No.	128	
Comm. Port	RS-485	
Baud Rate	1200bps, 2400bps, 4800bps, 9600bps, 19200bps	
Spectra Address	0~127	
Power Supply	24VAC	
Input Power	25W	
Operating Temp'	-25°C ~ 70°C	

FEATURES

- 1/4" SONY Super HAD CCD
- 480 TV Lines
- Integrated P/T/Z and Decoder
- Simplified Structure For High Stability & Reliability
- Multi Communication Protocol Supported, Baud Rate Programmable
- RS-485 Control
- Iris & Focus, Auto/ Manual
- Automatic Gain Control On/Off
- White Balance, Auto/ Manual
- Back Light Compensation, Auto/ Manual
- 12VDC
- Suitable Indoor and Outdoor Mount

MODEL NUMBERS

SVP-SDN18XI	In-Ceiling
SVP-SDN18XO	Outdoor



SURVEILUX®
The Art of Surveillance