



VEILUX®

INDOOR DAY & NIGHT NETWORK PTZ DOME CAMERA

SVPIP-52DN23X-I

SPECIFICATIONS

ITEM	SVPIP-52DN23X-I	
Signal System	NTSC	PAL
Image Sensor	1/4" Type SONY HAD CCD	
Effective Pixels	768 (H) x 494 (V) 380K	752 (H) x 582 (V) 440K
Horizontal Res.	More than 520TV Lines	More than 520TV Lines
Lens	23x Optical Zoom, F1.6 (Wide) - 3.8 (Tele), f=3.84 - 88.4mm	
Min Illumination	0.7Lux (30 IRE, AGC 34dB), 0.1Lux (Day&Night), 0.0007Lux (DSS)	
S/N	More than 49dB (AGC Off)	
Focus Mode	Auto/Manual/One Shot	
Back Light	On/Off	
AGC	Auto/8 - 38dB Selectable	
Electrical Shutter	1/60 - 1/10,000 sec 28 Steps	1/50 - 1/10,000 sec 28 Steps
Flickerless	Off/On (1/100 sec Shutter Set)	Off/On (1/120 sec Shutter Set)
Sharpness	Level 0-15	
Pan/Tilt Speed	Max Pan: 180° /sec / Tilt 90° /sec	
Vertical Tilt	+2° - 90°	
Home Position	On/Off	
Preset Point	250 Presets	
Video Output	Channel: 1 Ch, Compression: MPEG4, Resolution 704 x 480, Frame Rate 30Fps	
Audio (Optional)	Bi-Directional, Compression: G.723	
View Program	PC, PDA, Mobile Phone	
Network	Global/Private/Static/Dynamic IP, DDNS Support, Encryption (ID/Password/Image), Interface (10/100Mbps)	
Recording	Manual/Schedule/Motion Detection/Sensor Event	
Event & Alarm	Sensor Trigger/Motion Detection/Alarm Notification	
Connector	RJ 45, Power Supply	
API Support	Available	
Operating Temperature	-10°C to 50°	
Weight	About 3.2Kg	
Material	ABS, 6.6Inch Bubble (Poly-Carbonate)	
Dimension	224(H) x 189(D)mm	
Color	Back Box (Ivory), Clear Bubble	
Input Voltage	18~30 VAC, 24VAC (Nominal), Fuse 1.5A	
Power Supply	25W (Max)	



FEATURES

- 23x Optical Zoom Lens Integrated Web Speed Dome Camera
- Day & Night, Minimum Illumination 0.01Lux
- MPEG4 Compression with MPEG4, Multi-Streaming
- Dynamic IP Supported
- High Resolution Image Can Be Remotely Sent (704(H) x 480(V))
- User Friendly & Easy Surveillance, Monitoring, Searching, Control From Local or Remote Area



VEILUX®

The Art of Surveillance