



VEILUX®

DAY & NIGHT DOME IR CAMERA

SVV-54IR40L49



SPECIFICATIONS


ITEM	SVD-54IR40L49	
Signal System	NTSC	PAL
Image Sensor	1/3" SONY Super HAD CCD	
CCD Total Pixel	811(H) X 508(V) 410K	795(H) X 596(V) 470K
Scanning System	525Lines, 60fields/sec	625Lines, 50fields/sec
Min. Illumination	0.1Lux 5600 K F2.0 / 0.000Lux (IR LED ON)	
Lens	4~9mm DC Auto Iris	
Resolution	540 TV Lines	
S/N Ratio	More than 48db (AGC OFF)	
White Balance	ATW	
WB Range	ATW (2500~10000K)	
Electronic Shutter	1/60~1/100,000 sec.	1/50~1/100,000 sec
Video Output	1.0 Vp-p Composite video at 75ohm	
IR LED	40 Units Infrared LED, 20,000hrs 850nm(Optional)	
Gamma Correction	$\gamma=0.45$	
Beam Spread	36+56	
Night View Distance	Indoor 35m / Outdoor 20m	
Gain Control	AGC	
Operation Temp.	-20°C ~ 50°C	
Water Resistance	IP65	
Dimensions	160(Ø) x 130(L) mm	
Power Supply	12VDC / 640mA (Max)	
Cable	500mm BNC, DC Jack	
Weight	Approximately 3.25 pounds	



FEATURES

- 1/3" SONY Super HAD CCD
- 540 TV Lines
- Day & Night Function
- 3-Axis Gimbal
- External Control: Focus/Distance/DC Level/LED Level/ Flickerless, (Option)
- Back Light Compensation
- High Resolution: Vivid Sharp Picture
- Indoor: 35m: Outdoor: 20m
- 40 Units Infrared IR LED
- Rainproof (IP-65) / Dampproof
- 12VDC

DIMENSION



VEILUX®

The Art of Surveillance