



VEILUX®

TRUE DAY & NIGHT VANDAL RESISTANT IR DOME CAMERA

SVV-54IRC40L560



SPECIFICATIONS

ITEM	SVV-54IRC40L560	
TV System	NTSC	PAL
Image Sensor	1/3" SONY SuperHAD CCD	
CCD Total Pixel	410,000	470,000
Scanning System	525 Lines, 60 Fields/Sec	625 Lines, 50 Fields/Sec
Min. illumination	0.005Lux 5600 K F2.0 / 0.0001Lux (IR LED On)	
Lens	5~60mm 12X Optical Zoom Lens	
Resolution	540TV Lines	
S/N Ratio	48dB Min. (AGC Off)	
White Balance	ATW	
WB Range	ATW (2500~10000K)	
Electronic Shutter	1/60~1/100,000sec	1/50~1/100,000sec
Video Output	1.0Vp-p Composite Video At 75ohm	
IR LED	48 Units Infrared LED 20,000hrs 850nm (Option)	
Gamma Correction	$\gamma=0.45$	
Beam Spread	36° + 56°	
Night View Distance	Indoor 40m / Outdoor 20m	
Gain Control	AGC	
Operation Temp'	-20°C~50°C	
Water Resistance	IP-65	
Operation Hum'	Within 90% RH	
Dimensions	160(φ) x 120mm(L)	
Power Supply	12VDC	
Cable	1m BNC, AC Cable	

FEATURES

- 1/3" SONY Super HAD CCD
- High Resolution Over 540TV Lines (SONY HQ-1 DSP Built-In)
- True Day & Night (ICR Type-IR Cut Filter Removable)
- 3-Axis Gimbals
- Dwell Time Setting (Default 20 Sec)
- Back Light Compensation
- High Resolution: Vivid Sharp Picture
- Indoor: 40m / Outdoor: 20m
- 40 Units Infrared LED
- 5~60mm 12X Optical Zoom Lens
- Rainproof (IP-65)
- Dampproof
- 12VDC



VEILUX®

The Art of Surveillance