



VEILUX®

DUAL POWER COLOR DAY & NIGHT DOME CAMERA

SVV-58DNL2812D



SPECIFICATIONS

ITEM	SVV-58DNL2812D	
Signal System	NTSC	PAL
Image Sensor	1/3" SONY Super HAD CCD	
Sync. System	Internal	
CCD Total Pixel	811(H) x 508(V)	795(H) x 596 (V)
Effective Pixel No.	768(H) X 494(V) 380K	752(H) X 582(V) 440K
Scanning System	2:1 Interface	
Gamma Correction	$\gamma=0.45$	
Min. Illumination	0.002 Lux (Sens-up x 128)	
Lens	2.8~12mm DC Auto Iris	
Day & Night	Auto / On	
Resolution	580TV Lines (Color)	
S/N Ratio	More than 50db (AGC OFF)	
White Balance	ATW / AWC / Manual	
Back Light Comp'	Low, Middle, High, Off (Selectable)	
Gain Control	Low, Middle, High, Off (Selectable)	
Digital Noise Red'	Low, Middle, High, Off (Selectable)	
On-Screen Display	Built-in	
Electronic Shutter	1/60~1/120,000 sec.	1/50~1/120,000 sec
Motion Detection	On / Off Selectable (4 Zone)	
Privacy	On / Off Selectable (4 Zone)	
Mirror	On / Off (Selectable)	
Sharpness	On / Off (Level Adjustable)	
Video Output	CVBS: 1.0Vp-p composite video at 75ohm	
Operational Temp'	-20°C ~ 50°C	
Water Resistance	IP-65	
Dimensions	1160(Ø) x 120(H) mm	
Weight	About 960g	
Power Supply	12VDC / 24VAC Dual Voltage	
Cable	500mm BNC, DC Jack	

AGC Auto Gain Control
OFF **ON**



0.01 LUX



AWB Auto White Balance




VOLTAGE 12DC 24AC



BLC Back Light Compensation
OFF **ON**



580 TV LINES



DC AUTO IRIS



3-AXIS



MIRROR FUNCTION




VANDALPROOF



FEATURES

- 1/3" SONY Super HAD CCD
- 580 TV Lines
- 2.8~12mm DC Auto Iris
- Digital Noise Reduction (DNR)
- Privacy Function
- OSD (On-Screen Display)
- Min. Illumination: 0.002 Lux (Sens-up x 128)
- Day & Night (Electronic Changeable method)
- Electronic Light Control (ELC)
- Automatic Gain Control
- Automatic White Balance
- Back Light Compensation
- 3-Axis Gimbal
- 12VDC / 24VAC Dual Voltage
- Vandal Proof

DIMENSION



VEILUX®
The Art of Surveillance