





VEILUX®

DUAL POWER DAY & NIGHT DNR VANDAL PROOF DOME CAMERA

SVV-60DNL2812D

SPECIFICATIONS

ITEM	SVV-60DNL2812D	
Signal System	NTSC	PAL
Image Sensor	1/3" SONY SuperHAD II CCD	
Sync Internal	H/V 15.734 / 59.94 Hz	H/V 15.625 / 50 Hz
Sync Line Lock	H/V 15.750 / 60 Hz	H/V 15.625 / 50 Hz
Scanning System	2:1 Interlace	
Horizontal Resolution	600TV Lines (Max.) / 700TV Lines (B/W)	
Min. Illumination Sense-Up Off	0.12 Lux (15 IRE), 0.2 Lux (30 IRE), 0.4 Lux (50 IRE) F1.2	
Min. Illumination Sense-Up On	0.0002 Lux (15 IRE), 0.2 Lux (30 IRE), 0.4 Lux (50 IRE) F1.2	
Video Output	1.0Vp-p / 75ohm Video 0.714Vp-p	
Y Correction	0.45	
S/N	More than 52dB (AGC OFF)	
O.S.D.	Lens, E-Shutter, Backlight, WDR, AGC, Sens- Up, White Balance, Day & Night, Motion, Mirror, Sharpness, Gamma, Freeze, NEGA, DNR, D-Zoom, LSC, Eclipse, DIS, Privacy, Communi- cation, Sync, Camera-ID, Title	
Electrical Shutter	1/60~1/120,000	1/50~1/120,000
Privacy Masking	8 Windows (Polygonal, 8 Colors)	
Day & Night	Color / BW / Auto / EXT	
Motion Detection	Low, Middle, High, Off (Selectable)	
Digital Zoom	x1.0 ~ x10	
Sens-Up (Low Shut- ter)	Off ~ x512	
Sync	Auto / Internal / Digial Line Lock	
White Balance	ATW / AWC / Manual / Push	
WDR	On / Off (Step 1, Step 2, Step 3)	
3D-DNR	On / Off (Off, Low, Mid, High)	
LSC / DIS / Eclipse	On / Off	
AGC	Low / Middle / High / Off	
Lens	Aspherical 2.8~12mm DC Auto Iris Lens	
Oper Temp' / Hum'	-20°C ~ 60°C / 30% ~ 80%	
Storage Temp' / Hum'	-30°C ~ 60°C / 20% ~ 90%	
Power (Max.)	12VDC, 260mA / 24VAC, 170mA	
Dimension	145(Ø) x 106mm(H)	
Weight	About 1,040g	




FEATURES

- 1/3" SONY SuperHAD II CCD
- High Resolution 600TV Lines
- Day & Night
- WDR (Wide Dynamic Range)
- 3D-DNR (Digital Noise Reduction)
- Zero Defect
- Eclipse Function
- Motion Detection
- LSC (Lens Shading Compensation)
- Privacy Mask (Polygonal Mosaic)
- O.S.D. Menu Function
- 3-Axis Gimbal
- Sens-Up Function (x512)
- Internal / Line Lock Function
- Backlight Compensation
- DIS (Digital Image Stabilization)



DIMENSION



VEILUX®
The Art of Surveillance

3015 Eagle Drive, Suite 100, Grand Prairie, Texas 75052
Local Number: (214) 635-4855 / Fax: (928) 437-6270
sales@veilux.net
www.veilux.net