



VEILUX®

OBJECT AUTO-TRACKING DAY/NIGHT CAMERA

VP-ATDN36X



Surface



In-Ceiling



Outdoor



AWB Auto White Balance



BLC Back Light Compensation
OFF **ON**



**OPTICAL/
DIGITAL
ZOOM**



D&N
NIGHT **DAY**



**0.1
LUX**



VOLTAGE **24AC**



**540
TV LINES**



PAN/TILT/ZOOM

SPECIFICATIONS

ITEM	VP-ATDN36X	
Mounting Type	Surface, In-Ceiling, Wall, Pole	
Signal System	NTSC	PAL
Image Sensor	1/4" Sony Color CCD	
Resolution	540 TV Lines (Day) / 680 TV Lines (Night)	
Pan / Tilt Speed	Pan: 0.05°~400°/sec; Tilt: 0.03°~240°/sec	
S/N Ratio	More than 50db (AGC OFF)	
Min. illumination	0.1 Lux - Day / 0.01 Lux - Night	
IR Cut Filter	Yes	
Gain Control	Auto / Manual	
Back Light Comp'	Auto / Manual	
Optical Zoom	36x	
Digital Zoom	12x	
Lens	F1.6-F3.8 f=4-144mm	
Panning Range	Pan: 0°~360° Continuous ; Tilt: 0°~90°	
Preset Position No.	256	
Auto Cruise	Auto Switch from 0 to 54 Preset Pos' Sequentially	
Pattern Scan	P/T/Z Scan from 55 to 63 Preset Pos' Automatically	
Comm. Port	RS-485	
Baud Rate	1200bps, 2400bps, 4800bps, 9600bps, 19200bps	
Spectra Address	0~255	
Power Supply	24VAC 15W	
Track Speed	0°~100°/sec	

FEATURES

- Stabilized Images by Reducing Flickering
- Motion Auto Tracking, Intelligent Surveillance with Alarm Function
- Preset, Auto Cruise & Pattern Scan Function
- Multi Communication Protocol Supported, Baud Rate Programmable
- 360° Continuous Pan
- 0° to 9° Tilt From Horizontal Plane Auto Flip 180°
- Iris & Focus, Auto/ Manual
- White Balance, Auto/ Manual
- Back Light Compensation, Auto/ Manual
- Heater & Blower Included (Outdoor Only)
- Weatherproof (IP-66) - (Outdoor Only)

AVAILABLE MOUNTS

I-6	In-Ceiling Mount
W-6	Wall Mount
S-6	Surface Mount
P-6	Pendant Mount



VEILUX®
The Art of Surveillance

3015 Eagle Drive, Suite 100, Grand Prairie, Texas 75052
Local Number: (214) 635-4855 / Fax: (928) 437-6270
sales@veilux.net
www.veilux.net