

Product Specifications

PTZ-HN03100



This is hands down the best value for a PTZ in the industry. This is a Vandal Proof, Day/Night, PTZ camera. The camera features a super high 540TVL resolution, an on-screen display, IP-66 rating (with the outdoor wall mount), Auto Gain Control, Auto White Balance and many other features. This PTZ has 10x optical Zoom and 10X digital zoom allowing for a total of 100x zoom. It has built in day/night settings and can see in extremely low light. Connect this camera to any of

CAMERA

MODEL: PTZ-HN03100

VIDEO SIGNAL SYSTEM: NTSC

CCD: 1/4" Interline Transfer CCD

MAX PIXELS: 811(H) x 508(V) 410K

EFFECTIVE PIXELS: 768(H) x 494(V) 380K

HORIZONTAL 520 TV Lines (Color), 570

RESOLUTION: TV Lines (B/W)

S/N RATIO: 50dB (AGC Off)

ZOOM: 10X Optical, 10X Digital

FOCAL LENGTH: F1.8, 3.8 to 38mm

MIN. ILLUMINATION: 0.7 LUX (Color), 0.02 LUX (B/W) 50 IRE

DAY/NIGHT:

FOCUS: Auto/Day/Night (ICR)

IRIS: Auto/Manual

SHUTTER SPEED:

PAN/TILT

RANGE: Pan: 360 Degrees (Endless)

PAN/TILT/SPEED: Tilt: 180 (Auto Flip), 95 (Normal)

Preset: 36/sec

Manual 0.05~360/sec (proportional to zoom)

Swing: 1~180/sec

PRESET: 127 Presets (Label, Camera Image Setting)

SWING: 4 Patterns, 1200 Com-

GROUP: mands (about 5 minutes)

OTHER FUNCTIONS: 8 Groups (20 action entries per group)

GENERAL

COMMUNICATION: RS-485

PROTOCOL: Pelco-D, Pelco-P

PRIVACY ZONE: 4 Zone

ALARM INPUT: 4 Input

OSD: Menu/PTZ Info, etc.

RATED POWER: Indoor: 12VDC/.8A Outdoor: 12VDC/1.2A

DIMENSION: Dome: 4.21" Diameter

Housing: 5.57" Diameter x 5.01" Height