

Product Specifications

PTZ-LX550L3X



The PTZ-LX550L3X offers an affordable PTZ solution to enhance and expand the view of your surveillance system. With a super high 550TVL resolution and a built-in 5-15mm 3x zoom lens, this camera will satisfy most, if not all, of your PTZ requirements. High quality, weatherproof housing can be used indoors or outdoors and comes standard with a wall and a ceiling mount for even greater versatility and value.

MODEL:	PTZ-LX550L3X
DOME TYPE:	4" Indoor/Outdoor PTZ Dome, ABS Case
PROTOCOL:	Pelco-P/D
BAUDRATE:	1200/2400/4800/9600 bps
ADDRESS:	0-255
PAN ROTATION:	360 Continuous Rotation
TILT ROTATION:	0~90 Flip
MAX PAN SPEED:	60/Sec
MAX TILT SPEED:	30/Sec
PRESET SPEED:	100/Sec
PRESET ACCURACY:	± 3 ° Degrees
PRESET POINTS:	32 Points
PATTERN TOURS:	Programmable 16 Presets & Dwell Time / Speed
AUTO SCAN:	Yes (Programmable Speed & Left/Right Limited Point)
POWER-OFF MEMORY:	Current Setting & State (Inc. Pattern, Not Inc. AutoScan)
HOME POSITION:	Yes (Programmable Auto Return to Home Position)
ZOOM:	Optical 3X (4-9mm)
PROTECTION:	IP66 for Outdoor Use (Wall Mount)
OPERATING TEMPERATURE:	-5C~60C
POWER:	12V DC - 500mA
COMMUNICATION:	RS485 (+/-)