

TVIOB-PR2EXIR

2MP Prime Turbo HD WDR 1080P EXIR Bullet Camera

- 2 Megapixel high-performance CMOS
- True WDR, up to 120dB
- 3.6mm Fixed Lens
- EXIR technology, up to 131 feet IR distance



Megapixels:	2
Max Resolution:	1080p
Image Resolutions:	1080p (1920×1080)
Image Sensor:	2MP CMOS Image Sensor
Min Illumination:	0.01 Lux @ (F1.2,AGC ON), 0 Lux with IR
LEDs:	N/A
IR Distance:	131 feet
OSD:	Yes
Operating Temperature	-40°F to +140°F
Dimension:	3.41in x 3.23in x 8.67in
Power:	12V DC ±15%



TVIOB-PR2EXIR

HD1080P WDR EXIR Bullet Camera

Specifications

Camera	
Image Sensor	2MP CMOS Image Sensor
Signal System	PAL/NTSC
Effective Pixels	1928(H)*1088(V)
Min. illumination	0.01 Lux @ (F1.2,AGC ON), 0 Lux with IR
Shutter Time	1/25(1/30)s to 1/50,000s
Lens	3.6mm
	Angle of View: 82.2° (3.6mm)
Lens Mount	M12
Day & Night	ICR
Angle Adjustment	Pan: 0° - 360°; Tilt:0° - 90°; Rotate: 0° - 360°
Synchronization	Internal Synchronization
WDR	120dB
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 Analog HD output
S/N Ratio	>62dB
Menu	
AGC	Support
D/N Mode	Color/BW/SMART
White Balance	ATW/ MWB
BLC	Support
Functions	Wide Dynamic Range, Digital noise reduction, Mirror, SMART IR
General	
Operating Conditions	-40 °C – 60 °C (-40 °F – 140 °F), Humidity 90% or less (non-condensing)
Power Supply	12 VDC ± 15%
Power Consumption	Max. 5W
Protection Level	IP66
IR Range	Up to 40m
Communication	Up the coax, Protocol: HIKVISION-C (TVI output)
Dimensions	86.7mm×81.6mm×226mm (3.41"×3.23"×8.67")
Weight	Approx. 680g (1.5lb)

Dimensions

Unit: mm

