

TVIOB-PR2IR

2MP Prime Turbo HD Turret 1080P Mini Bullet Camera

- 2 Megapixel high-performance CMOS
- 3.6mm lens
- EXIR technology, up to 65 ft IR distance
- IP66 weatherproof



Megapixels:	2
Max Resolution:	1080p
Image Resolutions:	2MP (1920x1080) / 1.3M (1280x960) / 720P (1280x720) / D1 (704x576/704x480)
Image Sensor:	2MP CMOS Image Sensor
Min Illumination:	0.01 Lux @ (F1.2,AGC ON), 0 Lux with IR
LEDs:	N/A
IR Distance:	65 feet
OSD:	Yes
Operating Temperature	-40 °F – 140 °F, Humidity 90% or less (non-condensing)
Dimension:	2.3in x 2.19in x 6.05in
Power:	12V DC±15%

TVIOB-PR2IR

HD1080P WDR EXIR Bullet Camera

Specifications

Camera	
Image Sensor	2MP CMOS Image Sensor
Signal System	PAL/NTSC
Effective Pixels	1928(H)*1088(V)
Min. illumination	0.01 Lux @ (F1.2,AGC ON), 0 Lux with IR
Shutter Time	1/25s to 1/50,000s
Lens	3.6mm LENS@ F1.2
Lens Mount	M12
Day & Night	ICR
Angle Adjustment	Pan: 0° - 360°; Tilt:0° - 90°; Rotate: 0° - 360°
Synchronization	Internal Synchronization
WDR	120dB
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 Analog HD output
S/N Ratio	>62dB
Menu	
AGC	Support
D/N Mode	Color/BW/SMART
White Balance	ATW/ MWB
BLC	Support
Functions	Wide Dynamic Range, Digital noise reduction, Mirror, SMART IR
General	
Operating Conditions	-40 °C – 60 °C (-40 °F – 140 °F), Humidity 90% or less (non-condensing)
Power Supply	12 VDC±15%
Power Consumption	Max. 5W
Protection Level	IP66
IR Range	Up to 20m
Communication	Up the coax, Protocol: HIKVISION-C (TVI output)
Dimensions	58.5mm×55.5mm×153.6mm (2.30″×2.19″×6.05″)
Weight	Approx. 370g (0.82lb)

TVIOB-PR2IR

HD1080P WDR EXIR Bullet Camera

Dimensions Unit: mm

