

TVIOD-PR2IR28

Prime HD-TVI Over Coax 2MP 1080p IR Dome w/ 2.8mm Lens

- Up to 2 megapixel (1920 × 1080) resolution
- 2.8mm Fixed lens
- 65 feet IR (infrared) range
- IP66 weather rating



Megapixels:	2
Max Resolution:	1080p
Image Resolutions:	2MP (1920x1080) / 1.3M (1280x960) / 720P (1280x720) / D1 (704x576/704x480)
Image Sensor:	2MP CMOS Image Sensor
Min Illumination:	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
LEDs:	N/A
IR Distance:	65 feet
OSD:	Yes
Operating Temperature	40 °F – 140 °F, Humidity 90% or less (non-condensing)
Dimension:	3.58in x 3.25in x 2.69in
Power:	12V DC ±15%

TVIOD-PR2IR28

Prime HD Over Coax 2MP 1080p IR Dome w/ 2.8mm Lens

Specifications

Camera	
Image Sensor	2MP CMOS Image Sensor
Signal System	PAL/NTSC
Effective Pixels	1928(H)*1088(V)
Min. illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter Time	1/25s to 1/50,000s
Lens	2.8mm Lens @ F1.2
Lens Mount	M12
Day & Night	ICR
Angle Adjustment	Pan: 0° - 360°; Tilt:0° - 75°; Rotate: 0° - 360°
Synchronization	Internal Synchronization
WDR	> 120dB
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 Analog HD output
S/N Ratio	> 62dB
Menu	
AGC	Support
D/N Mode	Color/BW/SMART
White Balance	ATW/ MWB
BLC	Support
Functions	Wide Dynamic Range, Digital noise reduction, Mirror, SMART IR
General	
Operating Conditions	-40 °C – 60 °C (-40 °F – 140 °F), Humidity 90% or less (non-condensing)
Power Supply	12 VDC±15%
Power Consumption	Max. 5W
Protection Level	IP66
IR Range	Up to 20m
Communication	Up the coax, Protocol: HIKVISION-C (TVI output)
Dimensions	91mm×82.6mm×68.3mm (3.58"×3.25"×2.69")
Weight	Approx. 350g (0.77lb)

Dimensions

