

TVIOD-PRE2IR



2MP Prime Turbo HD 1080P Dome Camera

- 2 Megapixel high-performance CMOS
- 3.6mm lens
- Up to 65 ft IR distance
- IP66 weatherproof

Megapixels:	2
Max Resolution:	1080p
Image Resolutions:	2MP (1920x1080) / 1.3M (1280x960) / 720P (1280x720) / D1 (704x576/704x480)
Image Sensor:	1/2.7in Progressive Scan CMOS
Min Illumination:	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
LEDs:	12
IR Distance:	65 feet
OSD:	Yes
Operating Temperature	40 °F – 140 °F, Humidity 90% or less (non-condensing)
Dimension:	3.53in x 3.53in x 2.33n
Power:	12V DC

TVIOD-PRE2IR

2 MegaPixel Turbo Dome Camera

Specification

Model	TVIOD-PRE2IR
Parameter	Turbo HD1080p IR Turret Camera
Camera	
Image Sensor	1/2.7" Progressive Scan CMOS
Signal System	PAL/NTSC
Effective Pixels	1930(H)*1088(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter Time	1/25(1/30) s to 1/50,000 s
Lens	3.6mm Angle of View: 84.3°
Lens Mount	M12
Angle Adjustment	Pan: 0 - 360°, Tilt: 0 - 75°, Rotation: 0 - 360°
Day & Night	ICR
Synchronization	Internal synchronization
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 turbo HD output
S/N Ratio	More than 52dB
Menu	
AGC	Support
D/N Mode	Color/ BW/ EXT
White Balance	Auto/Manual
BLC	Support
Language	English/ Chinese
Functions	Digital noise reduction, Mirror
General	
Working Temperature/Humidity	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12V DC
Power Consumption	Max. 3W
Weather Proof Ratings	IP66
IR Range	Up to 65ft
Communication	Up the coax Protocol: HIKVISION-C(Coaxitron)
Dimension	89.6 × 59.1 mm (3.53" × 2.33")
Weight	240 g (0.53 lb)

TVIOD-PRE2IR

2 MegaPixel Turbo Dome Camera

Dimension

